



Product data sheet

Power tools for trade & industry

Rotary Hammer with SDS plus

GBH 3-28 DFR



Most versatile rotary hammer performance in the SDS plus category

The most important data

Rated input power	800 W
Impact energy (according to EPTA 05/2016)	3.1 J
Drilling dia. concrete, hammer drill bits	4 – 28 mm

Part Number 0 611 24A 060

[> More product information](#)

Technical data

Performance data

Impact rate at rated speed	0 – 4,000 bpm
Rated speed	0 – 900 rpm

Technical data

Rated input power	800 W
Impact energy (according to EPTA 05/2016)	3.1 J
Tool holder	SDS plus
Packaging dimensions (width x length x height)	357 x 475 x 125 mm
Voltage, electrical	110 V
Weight	3.6 kg

Drilling range

Drilling dia. concrete, hammer drill bits	4 – 28 mm
Opt. appl. range concrete, hammer drill bits	12 – 18 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	30 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	11.8 m/s ²
Uncertainty K	1.5 m/s ²

Chiselling in concrete

Vibration emission value ah	10 m/s ²
Uncertainty K	1.5 m/s ²

**BOSCH**

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Compact housing enables various applications in narrow and tight spaces
 - L-shaped design and Vibration Control for continuous effortless work
 - High power-to-weight ratio with 800 W motor and tool weight of 3.6 kg
-

