

**FILA INDUSTRIA CHIMICA S.P.A.**

Revision nr. 13

Dated 03/04/2019

Printed on 03/04/2019

Page n. 1/19

Replaced revision:12 (Dated: 14/03/2016)

FUGANET

Safety data sheet according to regulation (CE) n. 1907/2006 (REACH), Annex II, and successive adjustments introduced by Commission Regulation (EU) no. 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **FUGANET**
Chemical name and synonym **Detergent for joints**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Detergent for joints.**

| Identified Uses | Industrial | Professional | Consumer |
|-----------------|------------|--------------|----------|
| Uses | - | ✓ | ✓ |

1.3. Details of the supplier of the safety data sheet

Name **FILA INDUSTRIA CHIMICA S.P.A.**
Full address **Via Garibaldi, 58**
District and Country **35018 San Martino di Lupari (PD)
ITALIA**
Tel. **+39.049.9467300**
Fax **+39.049.9460753**

e-mail address of the competent person responsible for the Safety Data Sheet **sds@filasolutions.com**

1.4. Emergency telephone number

For urgent inquiries refer to **TEL +39.049.9467300 (Monday – Friday; 8.30 - 12.30 and 14.00 - 17.30)
UNITED KINGDOM: NHS Direct 111 (In England, Scotland North Ireland) 08454647 (Wales); IRELAND 018092166**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 **H319** Causes serious eye irritation.

2.2. Label elements



FUGANET

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P280 Wear eye protection / face protection.
P337+P313 If eye irritation persists: Get medical advice / attention.
P264 Wash hands thoroughly after handling.

5% or over but less than 15% soap

perfumes, Preservation agents, Linalool

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification 1272/2008 (CLP) |
|----------------|------------------|---|
| Phenylmethanol | | |
| CAS 100-51-6 | $6,5 \leq x < 8$ | Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319 |



FUGANET

EC 202-859-9

INDEX 603-057-00-5

Reg. no. 01-2119492630-38

Monoethanolamine oleate

CAS 2272-11-9

 $2 \leq x < 3$

Eye Irrit. 2 H319

EC 218-878-0

INDEX -

Reg. no. esente in accordo all'All. V
del REACH.**Propylene glycol n-propyl ether**

CAS 1569-01-3

 $2 \leq x < 3$

Flam. Liq. 3 H226, Eye Irrit. 2 H319

EC 216-372-4

INDEX -

Reg. no. 01-2119474443-37

ETHANOLAMINE

CAS 141-43-5

 $0,1 \leq x < 0,15$ Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B
H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Chronic 3 H412

EC 205-483-3

INDEX 603-030-00-8

Reg. no. 01-2119486455-28

**(1S)6,6-DIMETHYL-2-
METHYLENBICYCLOHEPTANE**

CAS 127-91-3

 $0 \leq x < 0,02$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Skin Sens. 1 H317,
Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC 204-872-5

INDEX -

Reg. no. 01-2119519230-54

Benzyl acetate

CAS 140-11-4

 $0 \leq x < 0,02$

Aquatic Chronic 3 H412

EC 205-399-7

INDEX -

Reg. no. 01-2119638272-42

**(1S)2,6,6-TRIMETHYLBICYCLO-2
HEPTENE**

CAS 7785-26-4

 $0 \leq x < 0,02$ Flam. Liq. 3 H226, Asp. Tox. 1 H304, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin
Sens. 1 H317, Aquatic Chronic 1 H410 M=1

EC 232-077-3

INDEX -

Reg. no. 01-2119979519-16

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove any contact lenses. Wash with warm water for at least 15 minutes, opening the eyelids well. Consult a doctor if the problem persists.
SKIN: Remove contaminated clothing. Wash with water. If irritation persists, consult a doctor. Wash the contaminated garments before reusing them.
INHALATION: Bring the subject to fresh air. If breathing is difficult, call a doctor immediately.

**FUGANET**

INGESTION: Consult a doctor. Induce vomiting only upon medical advice. Do not give anything by mouth if the person is unconscious and if not authorized by the doctor.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Stop the leak if there is no danger.

Wear appropriate protective equipment (including personal protective equipment referred to in section 8 of the safety data sheet) to prevent contamination of the skin, eyes and personal clothing. These indications are valid both for workers involved in the work and for emergency interventions.

Remove unequipped persons. Use an explosion-proof device. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) or heat from the area where the leak occurred.

6.2. Environmental precautions

Prevent the product from entering sewers, surface waters, water tables.

6.3. Methods and material for containment and cleaning up

For containment

**FUGANET**

Collect with absorbent substances (sand, diatomaceous earth, binder for acids, universal binder).

For the cleaning

After harvesting, wash the area and the materials involved with water, recovering the water used and, if necessary, sending it to disposal in authorized facilities.

6.4. Reference to other sections

Reference to other sections Personal protection: see section 8 Disposal considerations: see section 13

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

| | | |
|-----|-----------------|--|
| CZE | Česká Republika | Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci |
| DEU | Deutschland | TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte |
| DNK | Danmark | Graensevaerdier per stoffer og materialer |
| ESP | España | INSHT - Límites de exposición profesional para agentes químicos en España 2017 |
| FIN | Suomi | HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveysministeriön julkaisuja 2012:5 |
| FRA | France | JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits |
| GRC | Ελλάδα | ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012 |
| HRV | Hrvatska | NN13/09 - Ministarstvo gospodarstva, rada i poduzetništva |
| ITA | Italia | Decreto Legislativo 9 Aprile 2008, n.81 |
| NLD | Nederland | Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18 |
| NOR | Norge | Veiledning om Administrative normer for forurensning i arbeidsatmosfære |
| POL | Polska | ROZPORZĄDZENIE MINISTRA RODZIN Y, PRAC Y I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r |
| PRT | Portugal | Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diaro da Republica I 26; 2012-02-06 |
| ROU | România | Monitorul Oficial al României 44; 2012-01-19 |
| SVN | Slovenija | Uradni list Republike Slovenije 04.06.2015 (1602) - Pravilnik o spremembah in dopolnitvah Pravilnika o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu |
| SWE | Sverige | Occupational Exposure Limit Values, AF 2011:18 |
| EU | OEL EU | Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC. |
| | TLV-ACGIH | ACGIH 2018 |

BENZYL ALCOHOL

**FILA INDUSTRIA CHIMICA S.P.A.**

Revision nr. 13

Dated 03/04/2019

Printed on 03/04/2019

Page n. 6/19

Replaced revision:12 (Dated: 14/03/2016)

FUGANET**Threshold Limit Value**

| Type | Country | TWA/8h | | STEL/15min | |
|------|---------|--------|-----|------------|-----|
| | | mg/m3 | ppm | mg/m3 | ppm |
| TLV | CZE | 40 | | 80 | |
| AGW | DEU | 22 | 5 | 44 | 10 |
| HTP | FIN | 45 | 10 | | |
| NDS | POL | 240 | | | |

Predicted no-effect concentration - PNEC

| | | | | |
|--|--|------|--|-------|
| Normal value in fresh water | | 1 | | mg/l |
| Normal value in marine water | | 0,1 | | mg/l |
| Normal value for fresh water sediment | | 5,27 | | mg/kg |
| Normal value for marine water sediment | | 527 | | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | VND | 25 mg/kg/d | | | | | | |
| Inhalation | VND | 40,55 mg/m3 | | | VND | 450 mg/m3 | VND | 90 mg/m3 |
| Skin | VND | 28,5 mg/kg/d | VND | 5,7 mg/kg/d | VND | 47 mg/kg/d | VND | 9,5 mg/kg/d |

Monoethanolamine oleate**Predicted no-effect concentration - PNEC**

| | | | | |
|--|--|--------|--|-------|
| Normal value in fresh water | | 0,478 | | mg/l |
| Normal value in marine water | | 0,0478 | | mg/l |
| Normal value for fresh water sediment | | 8020 | | mg/kg |
| Normal value for marine water sediment | | 802 | | mg/kg |
| Normal value for water, intermittent release | | 0,141 | | mg/l |
| Normal value of STP microorganisms | | 0,562 | | mg/l |
| Normal value for the terrestrial compartment | | 1600 | | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | VND | 25 mg/kg bw/d | | | | | | |
| Inhalation | | | VND | 43,5 mg/m3 | | | VND | 146,9 mg/m3 |
| Skin | | | VND | 25 mg/kg bw/d | | | VND | 41,7 mg/kg bw/d |

1-propoxypropan-2-ol**Predicted no-effect concentration - PNEC**

| | | | | |
|--|--|--------|--|-------|
| Normal value in fresh water | | 0,1 | | mg/l |
| Normal value in marine water | | 0,01 | | mg/l |
| Normal value for fresh water sediment | | 0,386 | | mg/kg |
| Normal value for marine water sediment | | 0,0386 | | mg/kg |
| Normal value for water, intermittent release | | 1 | | mg/l |

**FILA INDUSTRIA CHIMICA S.P.A.**

Revision nr. 13

Dated 03/04/2019

Printed on 03/04/2019

Page n. 7/19

Replaced revision:12 (Dated: 14/03/2016)

FUGANET

Normal value of STP microorganisms 4 mg/l

Normal value for the terrestrial compartment 0,0185 mg/kg

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | VND | 26 mg/m3 | | | VND | 217 mg/m3 |
| Skin | | | VND | 2,2 mg/kg/d | | | VND | 9 mg/kg/d |

ETHANOLAMINE**Threshold Limit Value**

| Type | Country | TWA/8h | | STEL/15min | | |
|-----------|---------|--------|-----|------------|-----|------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | CZE | 2,5 | | 7,5 | | SKIN |
| MAK | DEU | 0,5 | 0,2 | 0,5 | 0,2 | |
| TLV | DNK | 2,5 | 1 | | | SKIN |
| VLA | ESP | 2,5 | 1 | 7,5 | 3 | SKIN |
| HTP | FIN | 2,5 | 1 | 7,6 | 3 | SKIN |
| VLEP | FRA | 2,5 | 1 | 7,6 | 3 | SKIN |
| WEL | GBR | 2,5 | 1 | 7,6 | 3 | SKIN |
| TLV | GRC | 2,5 | 1 | 7,6 | 3 | |
| GVI | HRV | 2,5 | 1 | 7,6 | 3 | SKIN |
| VLEP | ITA | 2,5 | 1 | 7,6 | 3 | SKIN |
| OEL | NLD | 2,5 | | 7,6 | | SKIN |
| TLV | NOR | 2,5 | 1 | | | SKIN |
| NDS | POL | 2,5 | | 7,5 | | |
| VLE | PRT | 2,5 | 1 | 7,6 | 3 | SKIN |
| TLV | ROU | 2,5 | 1 | 7,6 | 3 | SKIN |
| MV | SVN | 2,5 | 1 | 7,5 | 3 | SKIN |
| MAK | SWE | 8 | 3 | 15 | 6 | SKIN |
| OEL | EU | 2,5 | 1 | 7,6 | 3 | SKIN |
| TLV-ACGIH | | 7,5 | 3 | 15 | 6 | |

Predicted no-effect concentration - PNEC

Normal value in fresh water 0,085 mg/l

Normal value in marine water 0,0085 mg/l

Normal value for fresh water sediment 0,434 mg/kg

Normal value for marine water sediment 0,0434 mg/kg

Normal value for water, intermittent release 0,028 mg/l

Normal value of STP microorganisms 100 mg/l

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | VND | 3,75 mg/kg/d | | | | |

**FILA INDUSTRIA CHIMICA S.P.A.**

Revision nr. 13

Dated 03/04/2019

Printed on 03/04/2019

Page n. 8/19

Replaced revision:12 (Dated: 14/03/2016)

FUGANET

| | | | | |
|------------|---------------------|--------------|-----------------------|-----------|
| Inhalation | 2 mg/m ³ | VND | 3,3 mg/m ³ | VND |
| Skin | VND | 0,24 mg/kg/d | VND | 1 mg/kg/d |

(1S)6,6-DIMETHYL-2-METHYLENBICYCLOHEPTANE**Threshold Limit Value**

| Type | Country | TWA/8h | STEL/15min |
|------|---------|-------------------|------------|
| | | mg/m ³ | ppm |
| OEL | EU | 20 | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | | | | | | 5,98 mg/m ³ |

Benzyl acetate**Threshold Limit Value**

| Type | Country | TWA/8h | STEL/15min |
|------|---------|-------------------|------------|
| | | mg/m ³ | ppm |
| OEL | EU | 10 | |

(1S)2,6,6-TRIMETHYLBICYCLO-2 HEPTENE**Threshold Limit Value**

| Type | Country | TWA/8h | STEL/15min |
|------|---------|-------------------|------------|
| | | mg/m ³ | ppm |
| OEL | EU | 20 | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | | 5,98 mg/m ³ | | | | |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

TLV of solvent mixture: 7,5 mg/m³**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**FUGANET****HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following must be considered for the final choice of the work glove material: compatibility, degradation, break time and permeation.

In the case of preparations, the resistance of work gloves to chemical agents must be checked before use as unpredictable. The gloves have a wear time that depends on the duration and the mode of use

Recommended material: Nitrile, minimum 0.38 mm thickness or equivalent protective barrier material with a high level performance for continuous contact conditions, with a minimum permeability time of 480 minutes in accordance with the CEN EN 420 and EN standards 374.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|----------------------------------|----------------|
| Appearance | liquid |
| Colour | Light yellow |
| Odour | Pine fragrance |
| Odour threshold | Not available |
| pH | 10,5 |
| Melting point / freezing point | Not available |
| Initial boiling point | Not available |
| Boiling range | Not available |
| Flash point | > 93 °C |
| Evaporation Rate | Not available |
| Flammability of solids and gases | not applicable |
| Lower inflammability limit | Not available |
| Upper inflammability limit | Not available |
| Lower explosive limit | Not available |
| Upper explosive limit | Not available |
| Vapour pressure | Not available |

**FUGANET**

| | |
|--|-----------------|
| Vapour density | Not available |
| Relative density | Not available |
| Solubility | Readily soluble |
| Partition coefficient: n-octanol/water | Not available |
| Auto-ignition temperature | Not available |
| Decomposition temperature | Not available |
| Viscosity | Not available |
| Explosive properties | not applicable |
| Oxidising properties | not applicable |

9.2. Other information

VOC (Directive 2010/75/EC) : 9,61 % - 96,59 g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

BENZYL ALCOHOL

Decomposes at temperatures above 870°C/1598°F.Possibility of explosion.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

BENZYL ALCOHOL

May react dangerously with: hydrobromic acid,iron,oxidising agents,sulphuric acid.Risk of explosion on contact with: phosphorus trichloride.

ETHANOLAMINE

May react dangerously with: acrylonitrile,chloroepoxypropane,chlorosulphuric acid,hydrogen chloride,iron-sulphur compounds,acetic acid,acetic anhydride,mesityl oxide,nitric acid,sulphuric acid,strong acids,vinyl acetate,cellulose nitrate.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

BENZYL ALCOHOL

**FUGANET**

Avoid exposure to: air, sources of heat, naked flames.

ETHANOLAMINE

Avoid exposure to: air, sources of heat.

10.5. Incompatible materials

Oxidizing agents. Strong acids and bases.

BENZYL ALCOHOL

Incompatible with: sulphuric acid, oxidising substances, aluminium.

ETHANOLAMINE

Incompatible with: iron, strong acids, strong oxidants.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANOLAMINE

May develop: nitric oxide, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**FUGANET**

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:
> 20 mg/l
LD50 (Oral) of the mixture:
>2000 mg/kg
LD50 (Dermal) of the mixture:
Not classified (no significant component)

1-propoxypropan-2-ol

LD50 (Oral) > 2000 mg/kg Rat

LD50 (Dermal) > 2000 mg/kg Rat

ETHANOLAMINE

LD50 (Oral) 1515 mg/kg rat male/female

LD50 (Dermal) 2504 mg/kg male rabbit

BENZYL ALCOHOL

LD50 (Oral) 1230 mg/kg Rat

LD50 (Dermal) 2000 mg/kg Rabbit

LC50 (Inhalation) > 4,1 mg/l/4h Rat

Monoethanolamine oleate

LD50 (Oral) 1089 mg/kg rat male/female

LD50 (Dermal) 2504 mg/kg male rabbit

LC50 (Inhalation) > 1,3 mg/l/4h 6h rat male/female

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

**FUGANET**SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

1-propoxypropan-2-ol

LC50 - for Fish

> 100 mg/l/96h Rainbow Trout

EC50 - for Crustacea

> 100 mg/l/48h Daphnia Magna

ETHANOLAMINE

LC50 - for Fish

349 mg/l/96h Cyprinus carpio

EC50 - for Crustacea

65 mg/l/48h Daphnia Magna



FUGANET

EC50 - for Algae / Aquatic Plants 2,1 mg/l/72h Pseudokirchnerella subcapitata
Chronic NOEC for Fish 1,24 mg/l 41d Oryzias latipes

BENZYL ALCOHOL

LC50 - for Fish 460 mg/l/96h Pimephales promelas
EC50 - for Crustacea 230 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants 770 mg/l/72h Pseudokirchnerella subcapitata

Monoethanolamine oleate

LC50 - for Fish 349 mg/l/96h Cyprinus carpio
EC50 - for Crustacea 65 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants 2,5 mg/l/72h Pseudokirchnerella subcapitata

12.2. Persistence and degradability

1-propoxypropan-2-ol

Rapidly degradable
>70% 10d

ETHANOLAMINE

Solubility in water 1000 - 10000 mg/l
Rapidly degradable
>70% 28d

BENZYL ALCOHOL

Rapidly degradable
87% 28d

Monoethanolamine oleate

Rapidly degradable
>90% 21d

12.3. Bioaccumulative potential

ETHANOLAMINE

Partition coefficient: n-octanol/water -2,3

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1,05

12.4. Mobility in soil

ETHANOLAMINE

Partition coefficient: soil/water -0,5646

12.5. Results of PBT and vPvB assessment

**FUGANET**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards



FUGANET

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the

**FUGANET**

workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

Phenylmethanol

Propylene glycol n-propyl ether

ETHANOLAMINE

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|--------------------------|--|
| Flam. Liq. 3 | Flammable liquid, category 3 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Asp. Tox. 1 | Aspiration hazard, category 1 |
| Skin Corr. 1B | Skin corrosion, category 1B |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| Skin Sens. 1 | Skin sensitization, category 1 |
| Aquatic Acute 1 | Hazardous to the aquatic environment, acute toxicity, category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic toxicity, category 1 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment, chronic toxicity, category 3 |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H332 | Harmful if inhaled. |
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| H317 | May cause an allergic skin reaction. |
| H400 | Very toxic to aquatic life. |

**FILA INDUSTRIA CHIMICA S.P.A.**

Revision nr. 13

Dated 03/04/2019

FUGANET

Printed on 03/04/2019

Page n. 18/19

Replaced revision:12 (Dated: 14/03/2016)

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety



FILA INDUSTRIA CHIMICA S.P.A.

Revision nr. 13

Dated 03/04/2019

FUGANET

Printed on 03/04/2019

Page n. 19/19

Replaced revision:12 (Dated: 14/03/2016)

laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.