









Bridge and job site saw machini













































PACKAGE

- TECHNICAL CHARACTERISTICS





























- For cutting granite, marble, porcelain, single and double fired, bricks, cement, etc...
- Maximum length of cut: 155 cm (61").
- \bullet Maximum thickness of cut: 110 mm (4 1/3") in single pass; 235 mm (9 1/4") in double pass.
- Maximum blade diameter Ø 360 mm (14"); smallest blade diameter Ø 300 mm (12").
- \bullet Adjustable cutting depth. \bullet Tilting motor assembly for bevel cuts from 0° to 45°.
- Belt driven system optimizes motor torque and cutting capacity. Gear ratio of motor to disc $1.4 \div 1$. Drive belt type poly V.
- Cast and extruded aluminum framework.

- Easy-to-remove polypropylene tank for easy cleaning. Capacity: 38 lt (10 Gal).
- Heavy duty water pump and (2) jet nozzles provide superior blade cooling.
- Sliding motor assembly with cast aluminum housing provided with 4 re-adjustable pulleys (double bearings). Extruded aluminum rail.
- Re-adjustable square for long lasting precision.
- Telescopic legs provided with safety device to prevent collapsing.
- Pivoting blade guard remains parallel with tile to ensure maximum cutting depth.
- Floating blade guard remains in contact with tile to provide extra safety during operation.
- Equipped with: diamond disc Ø 350 mm (14") for porcelain tiles, wheels kit for easy transport, pressure device to hold tile, key kit, wrench, manual.

MODEL SPECIFICATIONS										
Part No.			N	TIME	M			•		(
420150A AP	8050532002692	1	230 V 50 Hz	2P+T / 16A	Single-phase	3 HP/2,2 kW	2800	300 mm	12"	2000
420150A 400P	8050532002739	1	400 V 50 Hz	● 3P+T+N / 16A	Three-phase	3 HP/ 2,2 kW	2800	300 mm	12"	2000
420150A 60HP	8050532002746	1	230 V 60 Hz	2P+T / 16A	Single-phase	3 HP/2,2 kW	3360	300 mm	12"	2400
420150A USP	8050532002715	1	110 V 60 Hz	● 2P+T / 16A + 🔡 UL	Single-phase	2,2 HP/1,65 kW	3360	300 mm	12"	2400
420150A GRP	8050532002760	1	110 V 50 Hz	OP₁T / 32A	Single-phase	2 2 HP/1 65 kW	2800	300 mm	12"	2000

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS / WEIGHT

Model	+(0)+	1										2
ZOE 150 ADV	350 mm 14"	110 11111	4 1/3"	80 mm	3 1/8"	155 cm	∞	109x109 cm	200x70x h95 cm	106 Kg	200x80x h110 cm	147 Kg 324 lbs







