



KERAQUICK SI ZERO

Mapei's flagship tile adhesive now with CO₂ fully offset in the entire life cycle





Keraquick S1 Zero

DESCRIPTION High-performance, quick-setting, deformable cementitious adhesive.

For the interior and exterior installation of ceramic and porcelain tiles and mosaics and natural stone not sensitive to moisture. For floors and walls with no vertical slip and very low emissions of VOC.


POT LIFE OF THE MIX	30 minutes	READY FOR USE	24 hours (3 days for swimming pools & water features)
OPEN TIME	15 - 20 minutes	STORAGE	12 months
SET TO LIGHT FOOT TRAFFIC	2 - 3 hours	CONSUMPTION	2-6 kg/m ²
COLOURS	Grey and white	PACKAGING	10 kg & 20 kg bags



RAPID SETTING
grouting after only 2 hours, light foot traffic after only 2 hours



UNDERFLOOR HEATING
suitable for use over underfloor heating systems



DEFORMABLE
S1 flexible, mix with **Latex Plus** for S2 flexibility for difficult substrates



SUSTAINABILITY
CO₂ emissions fully offset in the entire life cycle

AREAS OF USE



WHERE TO USE

- Interior and exterior use.
- Walls & Floors.
- Bathrooms, showers, kitchens, conservatories and on balconies and terraces.
- Swimming pools and industrial plants.
- Renovation in areas subject to intense traffic (airports, shopping centres, restaurants, showrooms etc.)

CERTIFICATIONS & TECHNOLOGIES



CO₂ emissions measured throughout the life cycle of products from the ZERO line in 2024, using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset through the acquisition of certified carbon credits in support of forestry protection projects. A commitment to the planet, to people and to biodiversity.





MAPEI UK LTD

Mapei House
Steel Park Road
Halesowen
West Midlands. B62 8HD
0121 508 6970
info@mapei.co.uk

MAPEI WORLD LONDON CITY

6 Great Sutton Street
Clerkenwell
London
ECTV 0BX
020 3302 9610
clerkenwell@mapei.co.uk