

CLEANING SEALING & AFTERCARE

CEMENT, GROUT & SALT RESIDUE REMOVER TECHNICAL DATA SHEET

REF: LTP/38



LTP CEMENT, GROUT & SALT RESIDUE REMOVER

Interior & Exterior use

For all types of **Unpolished Natural Stone**, glazed ceramic, polished & unpolished porcelain, slate, quarry tiles, brick, terracotta and granite.

A rapid action cleaning agent for removing cement residues, grout stain, salts, efflorescence and other similar deposits. May also be used in dilute or concentrated form. Does not affect chrome or stainless steel fixtures or fittings.

Directions for use:

Always test/practice on an inconspicuous area before proceeding to ensure that the finished result is satisfactory.

Shake container well before use.

In mild cases and on non-absorbent surfaces:

Dilute 1 part LTP Cement, Grout & Salt Residue Remover in 4 parts cool water. Apply with a cloth or sponge wrung out in the solution. Leave for up to 15 minutes. Extract released residues using a sponge and water.

In more severe cases:

Dilute 1 part LTP Cement, Grout & Salt Residue Remover in 1 part cool water. Apply liberally and spread over surface. If necessary, agitate with a nylon scrubber, scrubbing brush or rotary scrubbing machine and leave to react for 5-10 minutes, keeping surfaces wet with additional LTP Cement, Grout & Salt Residue Remover solution. Extract and rinse thoroughly with clean water.

In extremely severe cases:

Dampen the surface to be cleaned with water and apply undiluted. Agitate with a nylon scrubber, scrubbing brush or mechanical scrubber. Immediately extract and rinse thoroughly with clean water.

N.B. Always rinse surfaces thoroughly with cool clean water.

Coverage M² per application (approx.)

	1ltr	5ltr
Mild cases	30m ²	150m ²
More severe cases	10m ²	50m ²
Extremely severe	5m ²	25m ²

Storage information:

Store in a cool, dry, frost free environment ideally at 5 - 25°C
Shelf life up to 2 years if container is unopened.

Notes:

Not suitable for use on surfaces that are **polished**, (i.e. **polished marble, travertine or limestone**). Any contaminated surface should be rinsed off immediately with plenty of **clean water**. Do not use when under floor heating systems are in operation. Mask and protect any surface not to be cleaned.

Health, Safety & Environmental:

Causes skin irritation. Causes serious eye irritation

Keep out of reach of children. If medical advice is needed, have product container to hand. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.

UFI: 3K50-S0HF-H00R-DVCK



WARNING

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline

+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

