

































- Production capacity 300 Kg/h (50 lbs 100 lbs).
- Mixing at low rpms does not entrap air and provides a homogenous mix.
- Fixed paddle, rotating bucket. This system provides a higher level of operator safety and allows the operator to check the mix quality while mixing.
- \bullet Gear ratio of motor to bucket 25 \div 1.
- Supplied with: two buckets (45 lt/12 gal), standard mixing blade, hex key, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.			M	M				Lt
110	8024648003331	1	230 V 50/60 Hz	Single-phase	0,5 CV/0,37 kW	1400/1680	55 / 66	45 lt 12 gal
110 USA	8024648014092	1	110 V 60 Hz	Single-phase	0,5 CV/0,37 kW	1680	66	45 lt 12 gal
110 GB	8024648005403	1	110 V 50 Hz	Single-phase	0,5 CV/0,37 kW	1400	55	45 lt 12 gal

DIMENSIONS AND WEIGHT

DIMERSIONS AND TELOTIF													
Model		Ţ			\$								
	IPERBET	60x51xh 77 cm	23 5/8"x20"xh 30 1/4"	34 Kg	75 lbs	85x60xh 60 cm	33 1/2" x23 5/8" xh 23 5/8"	39 Kg	86 lbs				









PACKAGE