

Ref.: 58915 - 230v Ref : 58913 - 110v

#### USE

- Portable electric cutter with plunge effect (Vertical cut).
- Ideal for PROFESSIONAL cut of wall & floor ceramic tiles, included Porcelain Stoneware and other materials.
- Perfect for repairs and renovations.

#### FUNCTIONAL CHARACTERISTICS

- C<sup>3</sup> System Phyton cooling system combined with the Zero Dust system, keeps your work area clean by reducing the production of splashes.
- Incorporates a foldable tubular steel support with wheels to transport the machine easily.
- With lateral stop for repetitive cuts with adjustment from 0° to 45°.
- Magnetic holder for the blade wrench.
- CPX diamond blade for fast, smooth cuts with long life.



Is the customer's responsability to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropiate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.



# **OTHER CHARACTERISTICS**

- Laser pointer to facilitate the ceramic tile placement and obtain more precise cuts.
- Tilting cutting head adjusts for precise 22.5° and 45° bevel and mitre cuts.
- Plunge effect.
- Water tank with level indication min. and max. Maximum capacity: 5.02 gal / 19 L
- Aluminium main table with rubber surface. Table extensions, lateral and back, in reinforced plastic.
- Available in EU and UK versions.

### **TECHNICAL SPECIFICATIONS**

- Electric motor power: 1800 W
- Versions available:
  - o Ref. 58915: 220/240V 50-60 Hz UK
  - o Ref. 58913: 110/130V 50-60 Hz UK
- Machine weight: 45 kg
- Max. straight cutting length: 90x90 cm
- Max. diagonal cutting length: 60x60 cm
- Blade diameter: 250 mm
- Max. tile thickness: 90 mm

#### PACKAGING

- Pending information.





Is the customer's responsability to ensure, through their own trials and testing each product satisfies the purpose to which goes and if the actual conditions of use are the most appropriate • Specific values may be subject to variation, since fall outside our control because of the different conditions likely to be encountered in the use and application of our products • All data, information and recommendations contained in this product sheet, referred to products, way of use and applications, are based on actual knowledge • Data and the own technical sheet can be changed without prior notice.



# **DT-250 MAX**

# **STANDARDS**

- Directives:
  - o 2006/42/EC on Machinery
  - o 2014/35/EU on Low Voltage
  - o 2014/30/EU on Electromagnetic Compatibility
  - 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)
- Norms:
  - EN 60204-1:2018 Safety of machinery Electrical equipment of machines -Part 1: General requirements
  - EN 12418:2021 Masonry and stone cutting-off machines for job site Safety
  - EN 62841-1:2015 Electric motor-operated hand-held tools, transportable tools and lawn and garden machinery Safety
  - EN IEC 61000-6-4:2019 Electromagnetic compatibility (EMC) Part 6-4: Emission standard for industrial environments
  - EN IEC 61000-6-2:2019 Electromagnetic compatibility (EMC) Part 6-2: Immunity standard for industrial environments
  - EN IEC 61000-3-2:2019/A1:2021 Electromagnetic compatibility (EMC) Part 3-2: Limits
  - EN 61000-3-3: 2013+A1:2019 Electromagnetic compatibility (EMC) Part 3-3: Limits

