

BRIDGE AND JOB SITE SAW MACHINE







PACKAGE



TECHNICAL CHARACTERISTICS































- \bullet For cutting porcelain, single-double fired, marble and granite.
- Maximum length of cut 120 cm (47 1/4").
- Maximum depth of cut 100 mm (4") in single pass; 135 mm (5 1/3") in double pass. Diamond blade max Ø 350 mm (14"); min Ø 300 mm (12").
- Plunge cut and adjustable cutting depth.
- Heavy Duty water pump. High capacity double jet water cooling.
- Sliding bar and disc cover in aluminum.
- Easy-to-remove aluminum work benches for easy cleaning and maximum sturdiness.
- Coated metal frame.
- Re-adjustable aluminum square.
- Motor moves on 4 polypropylene pulleys.; each pulley is reinforced with 2 inside bearings.

- Pulleys are easy to re-adjust (tighten): avoid play and confer long lasting precision of cut.
- Motor assembly holder and pivots in galvanized steel.
- Tiling legs.
- Tilting movement (0-47°) for 45° angle cut (jolly).
- Available accessories: extra side square, self-standing side bench with rollers 4 wheels + 2 handles kit, wheel kit feed.
- Supplied with Ø 350 mm (14") diamond disc for porcelain tiles, user manual, keys kit, dressing stone.

MODEL SPECIFICATIONS

Part No.			M	M			•			
224MS 120EU	8024648088628	1	230V 50 Hz	Single-phase	3 HP / 2,2 kW	2800	300 mm 12"	2800		
224MS 120BR	8024648090522	1	230V 60 Hz	Single-phase	3 HP / 2,2 kW	3360	300 mm 12"	3360		
224MS 120HS	8024648090539	1	110V 60 Hz	Single-phase	2 HP / 1 5 kW	3360	300 mm 12"	3360		

CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS / WEIGHT

COTING SECTIONS AND MACHINE DIMENSIONS / WEIGHT													
Model	+(0))+	;		<u> </u>	\Rightarrow						1	
MISTRAL 120	350 mm	14"	100 mm	4" 2 3/3"	60 mm	2 3/8"	120 cm 47 1/4"	œ	85x85 cm	150x60x h60 cm	63 Kg 138 9 lbs	165x65x h72 cm 65"y25 17"y h 28 38"	83 Kg

