



SAFETY DATA SHEET ARDEX X 60 PU FLEX Part B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ARDEX X 60 PU FLEX Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Two-Part Reaction Resin Tile Adhesive

1.3. Details of the supplier of the safety data sheet

Supplier Ardex UK Limited
Homefield Road
Haverhill
Suffolk
CB9 8QP
01440 714939

Contact person safetydatasheets@ardex.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0) 870 190 6777 (24 hours)

National emergency telephone number ROI:- +353 (0)1 809 2166 (available 8am-10pm, 7 days)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Not Classified

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335 STOT RE 2 - H373

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

ARDEX X 60 PU FLEX Part B

Precautionary statements	<p>P102 Keep out of reach of children.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P284 [In case of inadequate ventilation] wear respiratory protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues, DIPHENYLMETHANE-4,4'-DI-ISOCYANATE, DIPHENYLMETHANE-2,4'-DI-ISOCYANATE
Supplementary precautionary statements	<p>P201 Obtain special instructions before use.</p> <p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P260 Do not breathe vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p> <p>P314 Get medical advice/ attention if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P405 Store locked up.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues	60-100%
CAS number: 9016-87-9	EC number: 618-498-9
Classification	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Resp. Sens. 1 - H334	
Skin Sens. 1 - H317	
Carc. 2 - H351	
STOT SE 3 - H335	
STOT RE 2 - H373	

ARDEX X 60 PU FLEX Part B

DIPHENYLMETHANE-2,4'-DI-ISOCYANATE			10-30%
CAS number: 5873-54-1	EC number: 227-534-9	REACH registration number: 01-2119480143-45-XXXX	
Classification			
Acute Tox. 4 - H332			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
Resp. Sens. 1 - H334			
Skin Sens. 1 - H317			
Carc. 2 - H351			
STOT SE 3 - H335			
STOT RE 2 - H373			
DIPHENYLMETHANE-4,4'-DI-ISOCYANATE			10-30%
CAS number: 101-68-8	EC number: 202-966-0	REACH registration number: 01-2119457014-47-XXXX	
Classification			
Acute Tox. 4 - H332			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
Resp. Sens. 1 - H334			
Skin Sens. 1 - H317			
Carc. 2 - H351			
STOT SE 3 - H335			
STOT RE 2 - H373			

The full text for all hazard statements is displayed in Section 16.

Composition comments Candidate List of Substances of Very High Concern Authorisation
This product contains no substances of very high concern in concentrations where an information obligation applies (REACH Regulation (EC) No. 1907/2006, Article 57).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Instantly remove any clothing soiled by the product
Inhalation	Take the person into the fresh air and keep him warm, let him rest; if there is difficulty in breathing, medical advice is required.
Ingestion	IF SWALLOWED: Do not induce vomiting. Get medical attention immediately.
Skin contact	Remove contamination with soap and water or recognised skin cleansing agent. Remove contaminated clothing. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	May cause sensitisation by inhalation.
Skin contact	May cause sensitisation by skin contact.

ARDEX X 60 PU FLEX Part B

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray. Carbon dioxide (CO₂). Alcohol-resistant foam. Powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO). Hydrogen cyanide (HCN). Nitrous gases (NO_x). Isocyanates.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Collect and dispose of spillage as indicated in Section 13.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Dispose of contents/container in accordance with local regulations. Neutralize with a solution of 5 - 10 % Sodium Carbonate, 0.2 -2 % detergents and 90 - 95 % water. Large Spillages: Pump off product.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Use only in well-ventilated areas. Provide adequate ventilation. Do not breathe gas, fume, vapours or spray. Protect from moisture. Clean contamination as soon as it occurs.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from moisture. Keep away from food, drink and animal feeding stuffs. Store away from the following materials: Acids.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

ARDEX X 60 PU FLEX Part B

8.1. Control parameters

Occupational exposure limits

DIPHENYLMETHANEDIISOCYANATE -Isomers & homologues

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³(Sen)

Short-term exposure limit (15-minute): WEL 0.07 mg/m³(Sen)

DIPHENYLMETHANE-2,4'-DI-ISOCYANATE

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³(Sen)

Short-term exposure limit (15-minute): WEL 0.07 mg/m³(Sen)

DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³(Sen)

Short-term exposure limit (15-minute): WEL 0.07 mg/m³(Sen)

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

Eye/face protection

Wear eye protection.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Wear suitable coveralls to prevent exposure to the skin.

Hygiene measures

Wash after use and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Gas and combination filter cartridges should comply with European Standard EN14387.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Brown.
Odour	Musty (mouldy).
Odour threshold	Not determined.
pH	Not applicable.
Initial boiling point and range	>300°C @ 1013 hPa
Flash point	~ 229°C
Evaporation rate	Not determined.

ARDEX X 60 PU FLEX Part B

Flammability (solid, gas)	Not applicable.
Vapour pressure	ca. 11 hPa @ 20°C ca. 20 hPa @ 50°C ca. 22 hPa @ 55°C
Relative density	~ 1.23 @ 20°C
Auto-ignition temperature	>500°C
Decomposition Temperature	Not determined.
Viscosity	ca. 145 mPa s @ 20°C
Oxidising properties	Not determined.

9.2. Other information

Other information Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The product reacts with water and will generate heat.

10.2. Chemical stability

Stability Stable at normal ambient temperatures. Polymerises at about 200 degrees Celsius with the evolution of carbon dioxide.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions The following materials may react with the product: Water, moisture. Forms CO₂. May generate heat.

10.4. Conditions to avoid

Conditions to avoid Water, moisture.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Acids. Alcohols. Amines. Alkalis. Water, moisture.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (dusts/mists mg/l) 1.5

Respiratory sensitisation

Respiratory sensitisation May cause sensitisation or allergic reactions in sensitive individuals. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

General information

Known or suspected carcinogen for humans.

Inhalation

Harmful if inhaled.

Ingestion

May cause stomach pain or vomiting.

ARDEX X 60 PU FLEX Part B

Skin contact Prolonged or repeated exposure may cause severe irritation. The liquid is irritating to eyes and skin.

Eye contact Irritation, burning, lachrymation, blurred vision after liquid splash.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hour: > 1000 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: > 1000 mg/l, Daphnia magna

Acute toxicity - aquatic plants ErC₅₀, 72 hours: > 1640 mg/l, Algae

Acute toxicity - microorganisms EC₅₀, 3 hours: > 100 mg/l, Activated sludge

12.2. Persistence and degradability

Persistence and degradability Not readily biodegradable.

Stability (hydrolysis) Reacts with water.

Biodegradation Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility No data available.

Henry's law constant 0.0229 Pa m³/mol @ °C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not applicable.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods For disposal, local regulations issued by the authorities must be observed. Dispose of liquid components at a suitable incineration plant. After curing, the product can be disposed of with household waste.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

ARDEX X 60 PU FLEX Part B

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Restrictions (Annex XVII Regulation 1907/2006)

This product contains substances subject to EU Regulation 1907/2006 (REACH) Annex XV11.

Diphenylmethane-4,4'-diisocyanate
CAS-No.: 101-68-8, EC-No.: 202-966-0
Subject to REACH Annex XV11, No. 56

Diphenylmethane-2,4'-diisocyanate
CAS-No.: 5873-54-1
Subject to REACH Annex XV11, No. 56

2,2'-Methylenediphenyl diisocyanate
CAS-No.: 2536-05-2, EC-No.: 219-799-4
Subject to REACH Annex XV11, No. 56

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	3
Issued by	UK Regulatory and Product Compliance Officer
Revision date	21/11/2021
Supersedes date	01/02/2019

ARDEX X 60 PU FLEX Part B

SDS number	20434
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.