

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

FUGALITE BIO PARQUET (A)

Date of first edition: 9/14/2022

Safety Data Sheet dated 22/11/2024

version 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: FUGALITE BIO PARQUET (A)

Trade code: 001012026 3 .013

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Filler; Restricted to professional users

Uses advised against: All uses other than recommended ones; Not intended for use by private individuals or non-professionals.

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel. +39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Ireland Poison information centre: 01 809 2166 (Daily 8am-10pm) In case of emergency call 999 or 112

Malta In case of emergency call: +356 2395 2000 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Skin Irrit. 2 Causes skin irritation.

Eye Irrit. 2 Causes serious eye irritation.

Skin Sens. 1A May cause an allergic skin reaction.

Repr. 1B May damage fertility.

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

DECL10 This titanium dioxide-containing product is not classified as carcinogen by inhalation because it does not meet the criteria stated in Note 10, Annex VI of Regulation (EC) 1272/2008.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Hazard pictograms and Signal Word



Danger

Hazard statements

H315 Causes skin irritation.

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H360F	May damage fertility.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye protection.
P280	Wear protective gloves and eye protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P501	Dispose of contents/container in accordance with applicable regulations.

Contains

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: FUGALITE BIO PARQUET (A)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
≥10-<20 %	bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS:1675-54-3 EC:216-823-5 Index:603-073-00-2	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411, M-Chronic:1	01-2119456619-26
			Specific Concentration Limits: C ≥ 5%: Eye Irrit. 2 H319 C ≥ 5%: Skin Irrit. 2 H315	
≥3-<5 %	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317; Repr. 1B, H360F	01-2119485289-22
≥1-<3 %	Titanium dioxide	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Not classified as hazardous	
≥1-<3 %	Alcohols, C12-15, branched and linear, ethoxylated	CAS:106232-83-1	Acute Tox. 4, H302; Eye Dam. 1, H318; Aquatic Chronic 3, H412	
≥0.5-<1 %	Quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372	
≥0.3-<0.5 %	1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl)	CAS:1065336-91-5 EC:915-687-0	Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Repr. 2, H361; Skin Sens. 1A, H317, M-Chronic:1, M-Acute:1	01-2119491304-40-XXXX

This mixture contains $\geq 1\%$ titanium dioxide (CAS 13463-67-7). The Annex VI classification of titanium dioxide does not apply to this mixture according to its Note 10.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- Remove contaminated clothing immediately and dispose off safely.
- After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation
Eye damages
Skin Irritation
Erythema

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

- None in particular.

5.2. Special hazards arising from the substance or mixture

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

5.3. Advice for firefighters

- Use suitable breathing apparatus .
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

- Wear personal protection equipment.
- Remove persons to safety.
- See protective measures under point 7 and 8.

For emergency responders:

- Wear personal protection equipment.

6.2. Environmental precautions

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Retain contaminated washing water and dispose it.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
- Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

- Suitable material for taking up: absorbing material, organic, sand
- Wash with plenty of water.

6.4. Reference to other sections

- See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Exercise the greatest care when handling or opening the container.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
Quartz CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m ³ (8h) R, A2 - Pulm fibrosis, lung cancer
	NATIONAL	AUSTRALIA	Long Term: 0.05 mg/m ³ Respirable fraction
	NATIONAL	HUNGARY	Long Term: 0.1 mg/m ³ Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL	INDIA	Long Term: 10 mg/m ³ (8h)
	NATIONAL	IRELAND	Long Term: 0.1 mg/m ³ Respirable fraction Source: 2021 Code of Practice
	NATIONAL	ITALY	Long Term: 0.1 mg/m ³ Polvere di silice cristallina respirabile (frazione inalabile). Rif:D.Lgs 81/2008 Source: D.lgs. 81/2008, Allegato XXXVIII
	NATIONAL	SPAIN	Long Term: 0.05 mg/m ³ Respirable fraction Source: LEP 2022
	NATIONAL	CROATIA	Long Term: 0.1 mg/m ³ Source: NN 1/2021
	NATIONAL	AUSTRIA	Long Term: 0.05 mg/m ³ MAK, III C, A Source: BGBl. II Nr. 156/2021
	NATIONAL	BELGIUM	Long Term: 0.1 mg/m ³ C Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	DENMARK	Long Term: 0.3 mg/m ³ Source: BEK nr 2203 af 29/11/2021
	NATIONAL	DENMARK	Long Term: 0.1 mg/m ³ EK Source: BEK nr 2203 af 29/11/2021
	NATIONAL	ESTONIA	Long Term: 0.1 mg/m ³ 1, C Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
	NATIONAL	FINLAND	Long Term: 0.05 mg/m ³ alveolijae, liite 3 Source: HTP-ARVOT 2020
	NATIONAL	FRANCE	Long Term: 0.1 mg/m ³

La VLEP s'applique à la fraction alvéolaire. Forme de silice cristalline.
Source: INRS outil65, article R. 4412-149 du Code du travail

NATIONAL	LITHUANIA	Long Term: 0.1 mg/m ³ Žiūrėti 1 priedo 3 punktą. Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NETHERLANDS	Long Term: 0.075 mg/m ³ (2) Source: Arbeidsomstandighedenregeling - Lijst B1
NATIONAL	NORWAY	Long Term: 0.3 mg/m ³ K 7 Source: FOR-2021-06-28-2248
NATIONAL	NORWAY	Long Term: 0.05 mg/m ³ K G 7 21 Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 0.1 mg/m ³ 6) Source: Dz.U. 2018 poz. 1286
NATIONAL	SWEDEN	Long Term: 0.1 mg/m ³ C, M, 3 Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 0.15 mg/m ³ TWA mg/m ³ : (a), C1A, SSC, P, Cancpulm Silicose / Lugenkrebs Silikose, HSE NIOSH OSHA Source: suva.ch/valeurs-limites
ACGIH		Long Term: 2.5 mg/m ³ (8h) Finescale particles; R ; A3 - LRT irr, pneumoconiosis
NATIONAL	AUSTRALIA	Long Term: 10 mg/m ³ (8h)
NATIONAL	GERMANY	Long Term: 0.3 mg/m ³ ; Short Term: 2.4 mg/m ³ DFG; Long term and short term: excluding ultrafine particles; respirable fraction; multiplied by the material density; Source: TRGS900
NATIONAL	BELGIUM	Long Term: 10 mg/m ³ Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 10 mg/m ³ U Source: NN 1/2021
NATIONAL	CROATIA	Long Term: 4 mg/m ³ R Source: NN 1/2021
NATIONAL	IRELAND	Long Term: 10 mg/m ³ Source: 2021 Code of Practice
NATIONAL	IRELAND	Long Term: 4 mg/m ³ Source: 2021 Code of Practice
NATIONAL	ROMANIA	Long Term: 10 mg/m ³ ; Short Term: 15 mg/m ³ Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SPAIN	Long Term: 10 mg/m ³ Source: LEP 2022
NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, MAK, A Source: BGBl. II Nr. 156/2021
NATIONAL	BULGARIA	Long Term: 10 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
NATIONAL	DENMARK	Long Term: 6 mg/m ³ K Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 5 mg/m ³ Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FRANCE	Long Term: 10 mg/m ³ Cancérogène de catégorie 2

Titanium dioxide
CAS: 13463-67-7

Quartz CAS: 14808-60-7		Source: INRS outil65
	NATIONAL GREECE	Long Term: 10 mg/m3 εισπν. Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL GREECE	Long Term: 5 mg/m3 αvapv. Source: ΦΕΚ 94/Α` 13.5.1999
	NATIONAL LATVIA	Long Term: 10 mg/m3 Source: KN325P1
	NATIONAL LITHUANIA	Long Term: 5 mg/m3 Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
	NATIONAL NORWAY	Long Term: 5 mg/m3 Source: FOR-2021-06-28-2248
	NATIONAL POLAND	Long Term: 10 mg/m3 4), 7) Source: Dz.U. 2018 poz. 1286
	NATIONAL SLOVAKIA	Long Term: 5 mg/m3 Source: 355 NARIADENIE VLÁDY z 10. mája 2006
	NATIONAL SWEDEN	Long Term: 5 mg/m3 3 Source: AFS 2021:3
	SUVA SWITZERLAND	Long Term: 3 mg/m3 TWA mg/m3: (a), SSC, Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
	WEL-EH40 UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m3 Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
	EU	Long Term: 0.1 mg/m3 Polvere di silice cristallina respirabile, frazione inalabile. (R), A2 - Pulm fibrosis, lung cancer. Directive 2017/2398
	ACGIH	Long Term: 0.025 mg/m3 (8h) R, A2 - Pulm fibrosis, lung cancer
	NATIONAL AUSTRALIA	Long Term: 0.05 mg/m3 (8h) Respirable fraction
	NATIONAL HUNGARY	Long Term: 0.1 mg/m3 (8h) Respirable aerosol Source: 5/2020. (II. 6.) ITM rendelet
	NATIONAL INDIA	Long Term: 10 mg/m3
	NATIONAL IRELAND	Long Term: 0.1 mg/m3 (8h) Respirable fraction Source: 2021 Code of Practice
	NATIONAL ITALY	Long Term: 0.1 mg/m3 (8h) Polvere di silice cristallina respirabile (frazione inalabile). D.Lgs 81/2008 Source: D.lgs. 81/2008, Allegato XXXVIII
	NATIONAL SPAIN	Long Term: 0.05 mg/m3 (8h) Respirable fraction Source: LEP 2022
	NATIONAL CROATIA	Long Term: 0.1 mg/m3 Source: NN 1/2021
	NATIONAL AUSTRIA	Long Term: 0.05 mg/m3 MAK, III C, A Source: BGBl. II Nr. 156/2021
	NATIONAL BELGIUM	Long Term: 0.1 mg/m3 C Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL DENMARK	Long Term: 0.3 mg/m3

		Source: BEK nr 2203 af 29/11/2021
NATIONAL	DENMARK	Long Term: 0.1 mg/m3 EK Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 0.1 mg/m3 1, C Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FINLAND	Long Term: 0.05 mg/m3 alveolijae, liite 3 Source: HTP-ARVOT 2020
NATIONAL	FRANCE	Long Term: 0.1 mg/m3 La VLEP s'applique à la fraction alvéolaire. Forme de silice cristalline. Source: INRS outil65, article R. 4412-149 du Code du travail
NATIONAL	LITHUANIA	Long Term: 0.1 mg/m3 Žiūrėti 1 priedo 3 punktą. Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NETHERLAND S	Long Term: 0.075 mg/m3 (2) Source: Arbeidsomstandighedenregeling - Lijst B1
NATIONAL	NORWAY	Long Term: 0.3 mg/m3 K 7 Source: FOR-2021-06-28-2248
NATIONAL	NORWAY	Long Term: 0.05 mg/m3 K G 7 21 Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 0.1 mg/m3 6) Source: Dz.U. 2018 poz. 1286
NATIONAL	SWEDEN	Long Term: 0.1 mg/m3 C, M, 3 Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 0.15 mg/m3 TWA mg/m3: (a), C1A, SSC, P, Cancpulm Silicose / Lugenkrebs Silikose, HSE NIOSH OSHA Source: suva.ch/valeurs-limites
Triiron tetraoxide CAS: 1317-61-9	NATIONAL	POLAND Long Term: 2.5 mg/m3; Short Term: 5 mg/m3 6) Source: Dz.U. 2018 poz. 1286
silicon dioxide, chemically prepared CAS: 7631-86-9	NATIONAL	AUSTRALIA Long Term: 2 mg/m3 This value is for inhalable dust containing no asbestos and < 1% crystalline silica
	NATIONAL	BELGIUM Long Term: 10 mg/m3 Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL	IRELAND Long Term: 6 mg/m3 Inhalable fraction Source: 2021 Code of Practice
	NATIONAL	IRELAND Long Term: 2.4 mg/m3 Respirable fraction Source: 2021 Code of Practice
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND Long Term: 6 mg/m3 Inhalable aerosol Source: EH40/2005 Workplace exposure limits
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND Long Term: 2.4 mg/m3 Respirable aerosol Source: EH40/2005 Workplace exposure limits

Aluminium oxide
CAS: 1344-28-1

NATIONAL	GERMANY	Long Term: 4 mg/m ³ DFG, 2, Y, E Source: TRGS 900
NATIONAL	SLOVENIA	Long Term: 4 mg/m ³ Y, (I) Source: UL št. 72, 11. 5. 2021
NATIONAL	AUSTRIA	MAK Source: BGBl. II Nr. 156/2021
NATIONAL	ESTONIA	Long Term: 2 mg/m ³ 1 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	LATVIA	Long Term: 1 mg/m ³ Source: KN325P1
SUVA	SWITZERLAND	SSC, Fibpulm / Lungenfibrose, Des VMEs se trouvent sous les substances associées / MAK-Werte finden sich unter den zugeordneten Stoffen Source: suva.ch/valeurs-limites
SUVA	SWITZERLAND	Long Term: 4 mg/m ³ TWA mg/m ³ : (I), SSC, Fibpulm / Lungenfibrose Source: suva.ch/valeurs-limites
NATIONAL	AUSTRALIA	Long Term: 10 mg/m ³ (8h) Inhalable dust containing no asbestos and < 1% crystalline silica
NATIONAL	BELGIUM	Long Term: 1 mg/m ³ Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
NATIONAL	CROATIA	Long Term: 10 mg/m ³ U Source: NN 1/2021
NATIONAL	CROATIA	Long Term: 4 mg/m ³ R Source: NN 1/2021
NATIONAL	ROMANIA	Long Term: 2 mg/m ³ ; Short Term: 5 mg/m ³ (Aerosoli) Source: Republicarea 1 - nr. 743 din 29 iulie 2021
NATIONAL	SPAIN	Long Term: 10 mg/m ³ véase Capítulo 9 Source: LEP 2022
NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, A Source: GKV, BGBl. II Nr. 156/2021
NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, MAK, A Source: GKV, BGBl. II Nr. 156/2021
NATIONAL	DENMARK	Long Term: 5 mg/m ³ Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 4 mg/m ³ 1 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FRANCE	Long Term: 10 mg/m ³ Source: INRS outil65
NATIONAL	GREECE	Long Term: 10 mg/m ³ εισπν Source: ΦΕΚ 94/Α` 13.5.1999
NATIONAL	GREECE	Long Term: 5 mg/m ³ αvapn Source: ΦΕΚ 94/Α` 13.5.1999
NATIONAL	HUNGARY	Long Term: 5 mg/m ³ N Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	HUNGARY	Long Term: 2 mg/m ³ resp, N

Source: 5/2020. (II. 6.) ITM rendelet

NATIONAL	LATVIA	Long Term: 6 mg/m3 Source: KN325P1
NATIONAL	LATVIA	Long Term: 4 mg/m3 Source: KN325P1
NATIONAL	NORWAY	Long Term: 10 mg/m3 1 Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 2.5 mg/m3 4) Source: Dz.U. 2018 poz. 1286
NATIONAL	POLAND	Long Term: 1.2 mg/m3 6) Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 4 mg/m3 10) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
SUVA	SWITZERLAND	Long Term: 3 mg/m3 TWA mg/m3: (a), B, Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
SUVA	SWITZERLAND	Long Term: 3 mg/m3; Short Term: 24 mg/m3 TWA mg/m3: (a), Fimétal / Metallrauch, NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m3 Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m3 Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
Diiron trioxide CAS: 1309-37-1	ACGIH	Long Term: 5 mg/m3 (8h) R, A4 - Pneumoconiosis
	NATIONAL AUSTRALIA	Long Term: 5 mg/m3 (8h)
	NATIONAL BELGIUM	Long Term: 5 mg/m3 Source: Code du bien-être au travail, Livre VI, Titre 1er, Annexe VI.1-1
	NATIONAL CROATIA	Long Term: 5 mg/m3; Short Term: 10 mg/m3 Source: NN 1/2021
	NATIONAL CROATIA	Long Term: 10 mg/m3 U Source: NN 1/2021
	NATIONAL CROATIA	Long Term: 4 mg/m3 R Source: NN 1/2021
	NATIONAL IRELAND	Long Term: 5 mg/m3; Short Term: 10 mg/m3 Source: 2021 Code of Practice
	NATIONAL IRELAND	Long Term: 10 mg/m3 Source: 2021 Code of Practice
	NATIONAL IRELAND	Long Term: 4 mg/m3 Source: 2021 Code of Practice
	NATIONAL ROMANIA	Long Term: 5 mg/m3; Short Term: 10 mg/m3 (Fumuri, pulberi) Source: Republicarea 1 - nr. 743 din 29 iulie 2021
	NATIONAL SPAIN	Long Term: 5 mg/m3 Source: LEP 2022

NATIONAL	AUSTRIA	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 60(Miw), 2x, MAK, A Source: GKV, BGBl. II Nr. 156/2021
NATIONAL	BULGARIA	Long Term: 5 mg/m ³ Source: НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г.
NATIONAL	DENMARK	Long Term: 3.5 mg/m ³ Source: BEK nr 2203 af 29/11/2021
NATIONAL	ESTONIA	Long Term: 3.5 mg/m ³ 1 Source: Vabariigi Valitsuse, 20. märtsi 2001. a määrus nr 105
NATIONAL	FINLAND	Long Term: 5 mg/m ³ Fe Source: HTP-ARVOT 2020
NATIONAL	FRANCE	Long Term: 5 mg/m ³ Source: INRS outil65
NATIONAL	GREECE	Long Term: 10 mg/m ³ ; Short Term: 10 mg/m ³ Source: ΦΕΚ 94/Α` 13.5.1999
NATIONAL	HUNGARY	Long Term: 4 mg/m ³ resp, T Source: 5/2020. (II. 6.) ITM rendelet
NATIONAL	LITHUANIA	Long Term: 3.5 mg/m ³ Žiūrėti 1 priedo 3 punktą. Source: 2011 m. rugsėjo 1 d. Nr. V-824/A1-389
NATIONAL	NORWAY	Long Term: 3 mg/m ³ Source: FOR-2021-06-28-2248
NATIONAL	POLAND	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ 4) Source: Dz.U. 2018 poz. 1286
NATIONAL	POLAND	Long Term: 2.5 mg/m ³ ; Short Term: 5 mg/m ³ 6) Source: Dz.U. 2018 poz. 1286
NATIONAL	SLOVAKIA	Long Term: 1.5 mg/m ³ 11) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SLOVAKIA	Long Term: 4 mg/m ³ 10) Source: 355 NARIADENIE VLÁDY z 10. mája 2006
NATIONAL	SWEDEN	Long Term: 3.5 mg/m ³ 3 Source: AFS 2021:3
SUVA	SWITZERLAND	Long Term: 3 mg/m ³ D TWA mg/m ³ : (a), Formel / Formal, NIOSH Source: suva.ch/valeurs-limites
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 5 mg/m ³ ; Short Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 10 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)
WEL-EH40	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	Long Term: 4 mg/m ³ Source: EH40/2005 Workplace exposure limits (Fourth Edition 2020)

Predicted No Effect Concentration (PNEC) values

bis-[4-(2,3-epoxipropoxy)phenyl] propane
CAS: 1675-54-3

Exposure Route: Fresh Water; PNEC Limit: 0.006 mg/l

Exposure Route: Marine water; PNEC Limit: 600 ng/L

Exposure Route: Freshwater sediments; PNEC Limit: 0.996 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 0.099 mg/kg

Exposure Route: Soil; PNEC Limit: 0.196 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.018 mg/l

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
CAS: 68609-97-2

Exposure Route: Fresh Water; PNEC Limit: 0.007 mg/l

Exposure Route: Marine water; PNEC Limit: 0.072 µg/l

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 66.77 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 6.677 mg/kg

Exposure Route: Soil; PNEC Limit: 80.12 mg/kg

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 0.072 mg/l

Titanium dioxide
CAS: 13463-67-7

Exposure Route: Fresh Water; PNEC Limit: 0.184 mg/l

Exposure Route: Marine water; PNEC Limit: 0.018 mg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 1 mg/kg

Exposure Route: Intermittent releases (marine water); PNEC Limit: 100 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/kg

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate
bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate
CAS: 1065336-91-5

Exposure Route: Fresh Water; PNEC Limit: 2.2 µg/l

Exposure Route: Intermittent releases (fresh water); PNEC Limit: 9 µg/l

Exposure Route: Marine water; PNEC Limit: 220 ng/L

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 1.05 mg/kg

Exposure Route: Marine water sediments; PNEC Limit: 110 µg/kg

Exposure Route: Soil; PNEC Limit: 210 µg/kg

Derived No Effect Level (DNEL) values

bis-[4-(2,3-epoxipropoxy)phenyl] propane
CAS: 1675-54-3

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects
Worker Professional: 0.75 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Worker Professional: 0.75 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 3.571 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
Worker Professional: 3.571 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 12.25 mg/m³

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 12.25 mg/m³

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.
CAS: 68609-97-2

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects
Worker Professional: 17 mg/kg; Consumer: 10 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects
Worker Professional: 29 mg/m³; Consumer: 7.6 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects
Consumer: 1219 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Short Term, local effects
Worker Professional: 68 mg/kg; Consumer: 40 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects
Worker Professional: 9.8 mg/m³; Consumer: 2.9 mg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 3.9 mg/kg; Consumer: 2.35 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 13.8 mg/m³; Consumer: 4.1 mg/m³

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 1 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects
Worker Professional: 1.7 mg/kg; Consumer: 1 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 0.98 mg/kg; Consumer: 1.46 mg/kg

Titanium dioxide
CAS: 13463-67-7
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects
Worker Professional: 10 mg/m³

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate
bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate
CAS: 1065336-91-5
Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects
Worker Professional: 680 µg/m³; Consumer: 170 µg/m³

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects
Worker Professional: 500 µg/kg; Consumer: 250 µg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects
Consumer: 50 µg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Chemical protection clothing. Safety shoes.

Protection for hands:

Suitable materials for safety gloves (EN 374, EN 16523-1:2015+A1:2018: Level 6):

Nitrile rubber - NBR: thickness ≥0,4mm; breakthrough time ≥480min.

Butyl rubber - IIR: thickness ≥0,4mm; breakthrough time ≥480min.

Respiratory protection:

Respiratory protective equipment should be worn when there is a possibility that the exposure limit value will be exceeded. In the absence of exposure limit values, respiratory protective equipment should be worn when adverse effects occur, such as respiratory irritation or discomfort, or if indicated by the results of your risk assessment. Use the following CE-approved air-purifying respirator: A-type organic vapour cartridge (boiling point >65°C)

Thermal Hazards:

Not expected if used as intended

Environmental exposure controls:

Prevent the product from entering sewers or surface and underground water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: In compliance with the product description

Odour: Odourless

Odour threshold: N.A.
pH: Not Relevant
Kinematic viscosity: N.A.
Melting point/freezing point: N.A.
Boiling point or initial boiling point and boiling range: 255 °C (491 °F)
Flash point: 120 °C (248 °F)
Lower and upper explosion limit: N.A.
Relative vapour density: N.A.
Vapour pressure: N.A.
Density and/or relative density: 1.54 g/cm³
Solubility in water: N.A.
Solubility in oil: N.A.
Partition coefficient n-octanol/water (log value): N.A.
Auto-ignition temperature: N.A.
Decomposition temperature: N.A.
Flammability: N.A.
Volatile Organic compounds - VOCs = 0 % ; 0 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Repr. 1B(H360)
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

bis-[4-(2,3-epoxipropoxy)phenyl] propane	a) acute toxicity	LD50 Oral Rabbit = 19800 mg/kg
---	-------------------	--------------------------------

		LD50 Skin Rabbit > 20 mg/kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Positive	epoxy resin with an average molecular mass ≤ 700 d irritate skin of rabbits
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	f) carcinogenicity	Genotoxicity Negative Carcinogenicity Oral Rat = 15 mg/kg Carcinogenicity Skin Rat = 1 mg/kg	Mouse, oral NOAEL NOAEL
	g) reproductive toxicity	No Observed Effect Level Oral Rat = 750 mg/kg	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	a) acute toxicity	LD50 Oral Rat = 26800 mg/kg	
		LC50 Inhalation Rat > 0.206 mg/l 4h LD50 Skin Rabbit > 4.5 ml/Kg 24h	
	b) skin corrosion/irritation	Skin Irritant Rabbit Yes	
	c) serious eye damage/irritation	Eye Irritant Rabbit Yes	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Positive	
	g) reproductive toxicity	No Observed Adverse Effect Level Skin Rat = 200 mg/kg	
Titanium dioxide	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg LC50 Inhalation > 6.82 mg/l LD50 Skin Rat > 2000 mg/kg	
	c) serious eye damage/irritation	Eye Corrosive Negative	
		Eye Irritant No	
	d) respiratory or skin sensitisation	Skin Sensitization Negative	
	i) STOT-repeated exposure	No Observed Adverse Effect Level 1000	
Alcohols, C12-15, branched and linear, ethoxylated	a) acute toxicity	LD50 Oral > 300 mg/kg	
Quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg	
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	a) acute toxicity	LD50 Oral Rat = 3230 mg/kg	
		LD50 Skin Rat > 3170 mg/kg	
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative 24h	
	c) serious eye damage/irritation	Eye Irritant Rabbit No	
	d) respiratory or skin sensitisation	Skin Sensitization Guinea pig Positive	
	f) carcinogenicity	Genotoxicity Negative	Mouse oral route

g) reproductive toxicity No Observed Adverse Effect Level Oral Rat = 30 mg/kg

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
bis-[4-(2,3-epoxipropoxy)phenyl]propane	CAS: 1675-54-3 - EINECS: 216-823-5 - INDEX: 603-073-00-2	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 2 mg/L 96h a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 1.8 mg/L 48h a) Aquatic acute toxicity : EC50 Algae Scenedesmus capricornutum = 11 mg/L 72h EPA-660/3-75-009 c) Bacteria toxicity : EC50 Sludge activated sludge = 100 mg/L 3h
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS: 68609-97-2 - EINECS: 271-846-8 - INDEX: 603-103-00-4	a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss > 5000 mg/L 96h a) Aquatic acute toxicity : NOEC Algae Pseudokirchneriella subcapitata = 500 mg/L 72h „OECD Guideline 201 (Alga, Growth Inhibition Test) a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 843 mg/L 72h c) Bacteria toxicity : EC50 Sludge > 100 mg/L
Titanium dioxide	CAS: 13463-67-7 - EINECS: 236-675-5 - INDEX: 022-006-00-2	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (Cavedano americano) > 1000 mg/L 96h a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata (alghe cloroficee) > 100 mg/L 72h a) Aquatic acute toxicity : NOEC Algae = 5600 mg/L a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna (Pulce d'acqua grande) > 100 mg/L 48h
Alcohols, C12-15, branched and linear, ethoxylated	CAS: 106232-83-1	a) Aquatic acute toxicity : LC50 Fish Carassius Auratus < 10 mg/L 96h CESIO a) Aquatic acute toxicity : EC50 Honeybees Daphnie < 10 mg/L 48h CESIO
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	CAS: 1065336-91-5 - EINECS: 915-687-0	a) Aquatic acute toxicity : LC50 Fish Danio rerio = 0.9 mg/L 96h OECD Guideline 203 b) Aquatic chronic toxicity : NOEC Daphnia Daphnia magna = 1 mg/L OECD guideline 211 a) Aquatic acute toxicity : EC50 Algae Desmodesmus subspicatus = 1.68 mg/L 72h OECD Guideline 201 a) Aquatic acute toxicity : EC20 Sludge activated sludge ≥ 100 mg/L 3h OECD guideline 209

12.2. Persistence and degradability

Component	Persitence/Degradability:	Test	Duration	Value	Notes:
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Non-readily biodegradable	Oxygen consumption			OECD Guideline 301 F (Ready Biodegradabil Manometric Respirom Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Readily biodegradable	Oxygen consumption		87.000	%; OECD Guideline 3 (Ready Biodegradabil Manometric Respirom Test)
Alcohols, C12-15, branched and linear, ethoxylated	Readily biodegradable		28d		>70% (OECD tg 301)
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	Non-readily biodegradable			38.000	28days

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Bioaccumulative	BCF - Bioconcentrantion factor	31.000
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Bioaccumulative	BCF - Bioconcentrantion factor	160.000
1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate	Not bioaccumulative		

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT or vPvB substances present in concentration >= 0.1%

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. Disposal through discharge into wastewater is not permitted

A waste code according to the European List of Wastes (LoW) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

The product disposed of as such, pursuant to Regulation (EU) 1357/2014, must be classified as hazardous waste

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID):

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A

ADR Excepted Quantities: N/A

Air (IATA):

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisions: N/A

Sea (IMDG):

IMDG-Stowage Code: N/A

IMDG-Stowage Note: N/A

IMDG-Subsidiary hazards: N/A

IMDG-Special Provisions: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 75

Provisions related to directive EU 2012/18 (Seveso III):

None

Explosives precursors – Regulation 2019/1148

No substances listed

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

2: Hazard to waters

German Lagerklasse according to TRGS 510:

LGK 10

SVHC Substances:

No SVHC substances present in concentration $\geq 0.1\%$

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

bis-[4-(2,3-epoxipropoxy)phenyl]propane

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

SECTION 16: Other information

Code	Description
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H360	May damage fertility or the unborn child in contact with skin and if swallowed.
H360F	May damage fertility.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.4.2/1B	Skin Sens. 1B	Skin Sensitisation, Category 1B
3.7/1B	Repr. 1B	Reproductive toxicity, Category 1B
3.7/2	Repr. 2	Reproductive toxicity, Category 2
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method

Skin Sens. 1A, H317	Calculation method
Repr. 1B, H360F	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAHF: Keep Away From Heat

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- SECTION 1: Identification of the substance/mixture and of the company/undertaking
- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 13: Disposal considerations
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Exposure Scenario

1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate
bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate

Exposure Scenario, 20/04/2022

Substance identity	
	1-Methyl 1,2,2,6,6-pentamethylpiperidin-4-yl decanedioate bis(1,2,2,6,6-pentamethylpiperidin-4-yl) decanedioate
CAS No.	1065336-91-5
EINECS No.	915-687-0

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC9a, PC9b)

1. ES 1		Widespread use by professional workers; Various products (PC9a, PC9b)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks - Use in rigid foams, coatings, adhesives and sealants		
Date - Version	20/04/2022 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Fillers, putties, plasters, modelling clay (PC9b)		
Environment Contributing Scenario			
CS1	ERC8c		
Worker Contributing Scenario			
CS2 Material transfers	PROC8a		
CS3 Rolling, Brushing	PROC10		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid			
Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases			
		Air - minimum efficiency of: 15 % Water - minimum efficiency of: 1 %	
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 88.9 %			
STP effluent (m³/day): 2000			
<i>Other conditions affecting environmental exposure</i>			
Local marine water dilution factor: 100 Local freshwater dilution factor: 10 Receiving surface water flow: 18000 m³/day Indoor use			
1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)			

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)	
<i>Product (article) characteristics</i>		
Physical form of product: Liquid		
Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa		
Concentration of substance in product: Covers percentage substance in the product up to 5 %.		
<i>Amount used, frequency and duration of use/exposure</i>		
Duration: Covers use up to 480 min		
Frequency: Covers use up to 5 days per week		
<i>Technical and organisational conditions and measures</i>		
Technical and organisational measures Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed. Ensure operatives are trained to minimise exposures.		
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>		
Personal protection		
Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.		Dermal - minimum efficiency of: = 90 %
Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin.		
<i>Other conditions affecting worker exposure</i>		
Indoor use Professional use		
<i>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.</i>		
Additional Good Practice Advice: Ensure no splashing occurs during transfer.		
1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)		
Process Categories	Roller application or brushing (PROC10)	
<i>Product (article) characteristics</i>		
Physical form of product: Liquid		
Vapour pressure: Vapour pressure < 0.01 Pa at standard temperature and pressure 0.0001 Pa		
Concentration of substance in product: Covers percentage substance in the product up to 5 %.		
<i>Amount used, frequency and duration of use/exposure</i>		
Duration: Covers use up to 480 min		
Frequency: Covers use up to 5 days per week		
<i>Technical and organisational conditions and measures</i>		
Technical and organisational measures		

Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed.
Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.	Dermal - minimum efficiency of: = 90 %
Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin.	

Other conditions affecting worker exposure

Indoor use
Professional use

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Ensure no splashing occurs during transfer.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario (ERC8c)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
soil	N/A	ECETOC TRA environment v2.0	0.0579

Additional information on exposure estimation:

Risk from environmental exposure is driven by soil.

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 0.2743 mg/kg bw/day	ECETOC TRA worker v3	= 0.137143
inhalative, systemic, long-term	= 0.4233 mg/m ³	ECETOC TRA worker v3	= 0.119924

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	= 0.5486 mg/kg bw/day	ECETOC TRA worker v3	= 0.274286
inhalative, systemic, long-term	= 0.274286 mg/m ³	ECETOC TRA worker v3	= 0.097

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario

bis-[4-(2,3-epoxipropoxy)phenyl]propane

Exposure Scenario, 07/06/2021

Substance identity	
	bis-[4-(2,3-epoxipropoxy)phenyl]propane
CAS No.	1675-54-3
INDEX No.	603-073-00-2
EINECS No.	216-823-5
Registration number	01-2119456619-26

Table of contents

1. **ES 1** Widespread use by professional workers; ESC2_0000001

1. ES 1		Widespread use by professional workers; ESC2_0000001	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks - Etching agent - Resins (prepolymers) - Adhesion promotor		
Date - Version	27/05/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	ESC2_0000001		
Article Category(ies)	Other articles made of stone, plaster, cement, glass or ceramic (AC4g)		
Environment Contributing Scenario			
CS1	ERC8c - ERC8f		
Worker Contributing Scenario			
CS2 Material transfers	PROC8a		
CS3 Rolling, Brushing	PROC10		
CS4 Roller, spreader, flow application	PROC11		
CS5 Mixing operations - Manual	PROC19		
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c, ERC8f)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) - Widespread use leading to inclusion into/onto article (outdoor) (ERC8c, ERC8f)		
<i>Product (article) characteristics</i>			
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
<i>Amount used, frequency and duration of use (or from service life)</i>			
Amounts used: Daily amount per site = 175 kg/day			
Release type: Continuous release			
Emission days: 365 days per year			
<i>Technical and organisational conditions and measures</i>			
Control measures to prevent releases Provide onsite wastewater removal efficiency of ³ (%):			
<i>Conditions and measures related to sewage treatment plant</i>			
STP type: Municipal Sewage Treatment Plant			
STP effluent (m³/day): 2			
<i>Conditions and measures related to treatment of waste (including article waste)</i>			
Waste treatment Dispose of waste cans and containers according to local regulations.			
<i>Other conditions affecting environmental exposure</i>			

Local marine water dilution factor: 100
Local freshwater dilution factor: 10
Receiving surface water flow: 18000 m³/day
Covers indoor and outdoor use

1.2. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Process Categories	Roller application or brushing (PROC10)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Process Categories	Non industrial spraying (PROC11)
---------------------------	----------------------------------

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Wear suitable face shield.

Wear an impervious suit.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.2. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)**Process Categories**

Manual activities involving hand contact (PROC19)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Avoid carrying out activities involving exposure for more than 1 hour per day.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear chemically resistant gloves (tested to EN374) in combination with "basic" employee training.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source**1.3. CS1: Environment Contributing Scenario (ERC8c, ERC8f)**

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	= 0.0022 mg/L	EUSES	= 0.00022
marine sediment	= 0.00127 mg/L	EUSES	= 0.0128
freshwater sediment	= 0.012 mg/L	EUSES	= 0.0369
marine water	= 2.34E-05 mg/L	EUSES	= 0.029
soil	= 0.00142 mg/kg dry weight	EUSES	= 0.00722

1.3. CS2: Worker Contributing Scenario: Material transfers (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.84 mg/m ³	ECETOC TRA worker v2.0	0.07
dermal, systemic, long-term	= 0.2742 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.03

1.3. CS3: Worker Contributing Scenario: Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 5E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 2.743 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.33

1.3. CS4: Worker Contributing Scenario: Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 0.36 mg/m ³	ECETOC TRA worker v2.0	0.03
dermal, systemic, long-term	= 2.68 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.32

1.3. CS5: Worker Contributing Scenario: Mixing operations - Manual (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 2E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 1.414 mg/kg bw/day	ECETOC TRA worker v3	< 0.42
combined routes, systemic, long-term	N/A	ECETOC TRA worker v3	= 0.42

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario

oxirane, mono[(c12-14-alkyloxy)methyl] derivs.

Exposure Scenario, 08/06/2021

Substance identity	
	oxirane, mono[(c12-14-alkyloxy)methyl] derivs.
CAS No.	68609-97-2
INDEX No.	603-103-00-4
EINECS No.	271-846-8
Registration number	01-2119485289-22

Table of contents

1. **ES 1** Widespread use by professional workers; Various products (PC1, PC9a, PC9b)

1. ES 1		Widespread use by professional workers; Various products (PC1, PC9a, PC9b)	
1.1 TITLE SECTION			
Exposure Scenario name	Professional application of coatings and inks by brush or roller - Professional application of coatings and inks		
Date - Version	07/04/2021 - 1.0		
Life Cycle Stage	Widespread use by professional workers		
Main user group	Professional uses		
Sector(s) of use	Professional uses (SU22)		
Product Categories	Adhesives, sealants (PC1) - Coatings and paints, thinners, paint removers (PC9a) - Fillers, putties, plasters, modelling clay (PC9b)		
Environment Contributing Scenario			
CS1		ERC8c	
Worker Contributing Scenario			
CS2 Mixing operations		PROC5	
CS3 Large surfaces - Surfaces - Rolling, Brushing		PROC10	
CS4 Large surfaces - Surfaces - Roller, spreader, flow application		PROC11	
CS5 Large surfaces - Surfaces - Rolling, Brushing		PROC19	
1.2 Conditions of use affecting exposure			
1.2. CS1: Environment Contributing Scenario (ERC8c)			
Environmental release categories	Widespread use leading to inclusion into/onto article (indoor) (ERC8c)		
Product (article) characteristics			
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP			
Amount used, frequency and duration of use (or from service life)			
Release type: Intermittent release			
1.2. CS2: Worker Contributing Scenario: Mixing operations (PROC5)			
Process Categories	Mixing or blending in batch processes (PROC5)		
Product (article) characteristics			
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP			
Concentration of substance in product: Covers percentage substance in the product up to 25 %.			
Amount used, frequency and duration of use/exposure			
Duration: Covers daily exposures up to 8 hours			
Technical and organisational conditions and measures			
Technical and organisational measures Ensure operatives are trained to minimise exposures. Avoid direct eye contact with product, also via contamination on hands.			
Conditions and measures related to personal protection, hygiene and health evaluation			
Personal protection Wear suitable gloves tested to EN374.			

Other conditions affecting worker exposure	
Indoor use Professional use Temperature: Covers use at ambient temperatures. Body parts exposed: Assumes that potential dermal contact is limited to hands and forearms.	
1.2. CS3: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC10)	
Process Categories	Roller application or brushing (PROC10)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 25 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Provide extract ventilation to points where emissions occur. Avoid direct eye contact with product, also via contamination on hands. Use long handled brushes and rollers.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140.	
Other conditions affecting worker exposure	
Indoor use Professional use Temperature: Covers use at ambient temperatures.	
1.2. CS4: Worker Contributing Scenario: Large surfaces - Surfaces - Roller, spreader, flow application (PROC11)	
Process Categories	Non industrial spraying (PROC11)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure < 0,5 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Frequency: For each use, avoid using for more than < 4 h/event	
Technical and organisational conditions and measures	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Provide extract ventilation to points where emissions occur. Avoid direct eye contact with product, also via contamination on hands. Use long handled brushes and rollers. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying.	
Conditions and measures related to personal protection, hygiene and health evaluation	

Personal protection

Wear suitable gloves tested to EN374.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.2. CS5: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC19)**Process Categories**

Manual activities involving hand contact (PROC19)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure < 0,5 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

For each use, avoid using for more than < 1 h/event

Technical and organisational conditions and measures**Technical and organisational measures**

Ensure operatives are trained to minimise exposures.

Provide extract ventilation to points where emissions occur.

Avoid direct eye contact with product, also via contamination on hands.

Use long handled brushes and rollers.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

Professional use

Temperature: Covers use at ambient temperatures.

1.3 Exposure estimation and reference to its source**1.3. CS2: Worker Contributing Scenario: Mixing operations (PROC5)**

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	= 9.3 mg/m ³	ECETOC TRA worker v2.0	= 0.674
dermal, systemic, long-term	= 0.007 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.002

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS3: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, local, short-term	= 2.325 mg/m ³	ECETOC TRA worker v2.0	= 0.168
dermal, systemic, long-term	= 0.137 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.035

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS4: Worker Contributing Scenario: Large surfaces - Surfaces - Roller, spreader, flow application (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, short-term	= 0.36 mg/m ³	ECETOC TRA worker v2.0	= 0.03
dermal, systemic, long-term	= 2.68 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.32

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.3. CS5: Worker Contributing Scenario: Large surfaces - Surfaces - Rolling, Brushing (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, local, long-term	= 2E-07 mg/m ³	ECETOC TRA worker v2.0	< 0.001
dermal, systemic, long-term	= 1.414 mg/kg bw/day	ECETOC TRA worker v2.0	= 0.42

Additional information on exposure estimation:

If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374.

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Article 31, Annex II, as amended by Commission Regulation (EU) 2020/878

FUGALITE BIO PARQUET (B)

Date of first edition: 9/14/2022

Safety Data Sheet dated 5/16/2023

version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: FUGALITE BIO PARQUET (B)

Trade code: 001012027 3 .091

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: hardener

Uses advised against: All uses other than recommended ones

1.3. Details of the supplier of the safety data sheet

Company: KERAKOLL S.p.A.

Via dell'Artigianato, 9

41049 Sassuolo (MODENA) - ITALY

Tel. +39 0536 816511 Fax. +39 0536816581

safety@kerakoll.com

1.4. Emergency telephone number

European emergency phone number 112

Kerakoll Italy (+39) 0536 816511

Ireland

Poison information centre: (+353) 809 2166 (Daily 8am-10pm)

In case of emergency call 999 or 112

Malta

In case of emergency call: 112 (24h)

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Eye Dam. 1 Causes serious eye damage.

Skin Sens. 1A May cause an allergic skin reaction.

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Danger

Hazard statements

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P280 Wear protective gloves and eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with applicable regulations.

Contains

Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

PHENOL, 4,4-(1-METHYLETHYLIDENE)BIS-, POLYMER WITH N-(2-AMINOETHYL)-1,2-ETHANEDIAMINE,(CHLOROMETHYL)OXIRANE, ALPHA-HYDRO-OMEGA-HYDROXYPOLY[OXY(METHYL-1,2-ETHANEDIYL)] ETHER WITH2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL (4:1) OXIRANYLMETHYL ETHER, AND ME

Alcohols, C12-15, branched and linear, ethoxylated

Amines, polyethylenepoly-, tetraethylenepentamine fraction

POLYETHYLENE POLYAMINE, PENTAETHYLENEHEXAMINE FRACTION

Amines, polyethylenepoly-, triethylenetetramine fraction

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: FUGALITE BIO PARQUET (B)

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
10-19,9 %	PHENOL, 4,4-(1-METHYLETHYLIDENE)BIS-, POLYMER WITH N-(2-AMINOETHYL)-1,2-ETHANEDIAMINE, (CHLOROMETHYL)OXIRANE, ALPHA-HYDRO-OMEGA-HYDROXYPOLY[OXY(METHYL-1,2-ETHANEDIYL)] ETHER WITH2,2-BIS(HYDROXYMETHYL)-1,3-PROPANEDIOL (4:1) OXIRANYLMETHYL ETHER, AND ME	CAS:455946-46-0	Eye Dam. 1, H318	
1-2,4 %	Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS:68082-29-1 EC:500-191-5	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Sens. 1A, H317, M-Chronic:1	01-2119972320-44
1-2,4 %	Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	EC:701-046-0	Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317; Aquatic Chronic 2, H411, M-Chronic:1	01-2119972321-42
1-2,4 %	Alcohols, C12-15, branched and linear, ethoxylated	CAS:106232-83-1	Acute Tox. 4, H302; Eye Dam. 1, H318; Aquatic Chronic 3, H412	
< 1 %	Amines, polyethylenepoly-, tetraethylenepentamine fraction	CAS:90640-66-7 EC:292-587-7	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1B, H314; Skin Sens. 1,1A,1B, H317; Eye Dam. 1, H318; Aquatic Chronic 2, H411	01-2119487290-37

< 1 %	POLYETHYLENE POLYAMINE, PENTAETHYLENEHEXAMINE FRACTION	EC:701-266-7	Skin Corr. 1B, H314; Acute Tox. 4, 01-2119485826-22 H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410, EUH071
< 0,5 %	Quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372
< 0,5 %	titanium dioxide	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Carc. 2, H351
< 0,5 %	Amines, polyethylenepoly-, triethylenetetramine fraction	CAS:90640-67-8 EC:292-588-2 Index:612-059-00-5	Acute Tox. 4, H312; Acute Tox. 4, 01-2119487919-13 H302; Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412; Eye Dam. 1, H318

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

- Immediately take off all contaminated clothing.
- OBTAIN IMMEDIATE MEDICAL ATTENTION.
- Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

- After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
- Protect uninjured eye.

In case of Ingestion:

- Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

Eye irritation

Eye damages

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

- Water.
- Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

- None in particular.

5.2. Special hazards arising from the substance or mixture

- Do not inhale explosion and combustion gases.
- Burning produces heavy smoke.

5.3. Advice for firefighters

- Use suitable breathing apparatus .
- Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
- Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- Wear personal protection equipment.
- Remove persons to safety.
- See protective measures under point 7 and 8.

6.2. Environmental precautions

- Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
- Retain contaminated washing water and dispose it.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
- Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

Component	OEL Type	Country	Ceiling	Long Term mg/m ³	Long Term ppm	Short Term mg/m ³	Short Term ppm	Notes
Quartz	NATIONAL	AUSTRALIA		0.050				Respirable fraction
	NATIONAL	AUSTRIA		0.050				MAK value, Respirable fraction
	NATIONAL	BELGIUM		0.100				Respirable dust , Additional indication "C" means that the agent falls within the scope of Title 2 concerning carcinogenic, mutagenic and reprotoxic agents of Book VI of the Codex on well-being at work
	NATIONAL	DENMARK		0.300		0.600		Inhalable aerosol
	NATIONAL	DENMARK		0.100		0.200		Respirable aerosol
	NATIONAL	FINLAND		0.050				Respirable fraction
	NATIONAL	FRANCE		0.100				Respirable aerosol
	NATIONAL	HUNGARY		0.100				Respirable fraction
	NATIONAL	IRELAND		0.100				Respirable fraction
	NATIONAL	SPAIN		0.050				Respirable fraction
	NATIONAL	SWEDEN		0.100				Respirable fraction
	NATIONAL	SWITZERLAND		0.150				Respirable aerosol
	NATIONAL	NETHERLANDS		0.075				Respirable fraction
	NATIONAL	ITALY		0.100				Polvere di silice cristallina respirabile (frazione inalabile). Rif:D.Lgs 81/2008
	NATIONAL	INDIA		10.000				
	NATIONAL	POLAND		0.100				Respirable fraction Dz. U. 2018 poz. 1286 wraz z późn. zm.
	NATIONAL	PORTUGAL		0.050				Respirable fraction
	NATIONAL	SLOVENIA		0.050	0.400			

Calcium carbonate	NATIONAL	AUSTRALIA	10.000					This value is for inhalable dust containing no asbestos and <1 % crystalline silica.
	NATIONAL	FRANCE	10.000					inhalable aerosol
	NATIONAL	HUNGARY	10.000					inhalable aerosol
	NATIONAL	IRELAND	10.000					Inhalable fraction
	NATIONAL	IRELAND	4.000					Respirable fraction
	NATIONAL	LATVIA	6.000					
	NATIONAL	POLAND	10.000					
	NATIONAL	SWITZERLAND	3.000					respirable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000					inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4.000					respirable aerosol
	NATIONAL	BELGIUM	10.000					
	NATIONAL	CROATIA	10.000					
	NATIONAL	NETHERLANDS	10.000					
	NATIONAL	PORTUGAL	10.000					
	NATIONAL	SPAIN	10.000					
benzyl alcohol	NATIONAL	FINLAND	45.000	10.000				
	NATIONAL	GERMANY	22.000	5.000	44.000	10.000		AGS; Long term and short term: inhalable fraction
	NATIONAL	GERMANY	22.000	5.000	44.000	10.000		DFG; Long term and short term: inhalable fraction
	NATIONAL	LATVIA	5.000					
	NATIONAL	SWITZERLAND	5.000	22.000				
	NATIONAL	BULGARIA	5.000					
	NATIONAL	CZECHIA	40.000		80.000			
	NATIONAL	LITHUANIA	5.000					
	NATIONAL	POLAND	240.000					Dz. U. 2018 poz. 1286 wraz z późn. zm
	NATIONAL	SLOVENIA	22.000	5.000	44.000	10.000		
Quartz	NATIONAL	AUSTRALIA	0.050					Respirable fraction
	NATIONAL	AUSTRIA	0.050					respirable fraction
	NATIONAL	BELGIUM	0.100					Respirable dust , Additional indication "C" means that the agent falls within the scope of Title 2 concerning carcinogenic, mutagenic and reprotoxic agents of Book VI of the Codex on well-being at work
	NATIONAL	DENMARK	0.300		0.600			Inhalable aerosol
	NATIONAL	DENMARK	0.100		0.200			Respirable aerosol
	NATIONAL	FINLAND	0.050					Respirable fraction
	NATIONAL	FRANCE	0.100					Respirable aerosol
	NATIONAL	HUNGARY	0.100					Respirable aerosol

titanium dioxide	NATIONAL	IRELAND	0.100		Respirable fraction
	NATIONAL	SPAIN	0.050		Respirable fraction
	NATIONAL	SWEDEN	0.100		Respirable aerosol
	NATIONAL	SWITZERLAND	0.150		Respirable aerosol
	NATIONAL	NETHERLANDS	0.075		Respirable dust
	NATIONAL	ITALY	0.100		Polvere di silice cristallina respirabile (frazione inalabile). D.Lgs 81/2008
	NATIONAL	CROATIA	0.100		
	NATIONAL	ESTONIA	0.100		
	NATIONAL	LITHUANIA	0.100		
	NATIONAL	POLAND	0.100		Respirable fraction Dz. U. 2018 poz. 1286 wraz z późn. zm.
	NATIONAL	PORTUGAL	0.050		
	NATIONAL	SLOVENIA	0.050	0.400	
	EU	NNN	0.100		Polvere di silice cristallina respirabile, frazione inalabile. (R), A2 - Pulm fibrosis, lung cancer. Directive 2017/2398
	NATIONAL	INDIA	10.000		
	NATIONAL	AUSTRALIA	10		
	NATIONAL	BELGIUM	10.000		
	NATIONAL	DENMARK	6.000	12.000	Long term and short term: total dust
	NATIONAL	FRANCE	11.000		Inhalable aerosol
	NATIONAL	GERMANY	0.300	2.400	DFG; Long term and short term: excluding ultrafine particles; respirable fraction; multiplied by the material density;
	NATIONAL	IRELAND	10.000		Inhalable fraction
	NATIONAL	IRELAND	8.000		Respirable fraction
	NATIONAL	LATVIA	10.000		
	NATIONAL	POLAND	10.000	30.000	Dz. U. 2018 poz. 1286 wraz z późn. zm
	NATIONAL	ROMANIA	10.000	15.000	
	NATIONAL	SPAIN	10.000		Inhalable aerosol
	NATIONAL	SWEDEN	5.000		Inhalable aerosol
	NATIONAL	SWITZERLAND	3.000		Respirable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4.000		Respirable aerosol
	NATIONAL	AUSTRIA	5.000	10.000	
	NATIONAL	BULGARIA	10.000		
	NATIONAL	CROATIA	10.000		total dust

silicon dioxide, chemically prepared	NATIONAL	CROATIA	4.000		respirable dust
	NATIONAL	GREECE	10.000		
	NATIONAL	GREECE	50.000		
	NATIONAL	GREECE	5.000		
	NATIONAL	LITHUANIA	5.000		
	NATIONAL	PORTUGAL	10.000		
	NATIONAL	SLOVAKIA	5.000		
	NATIONAL	SLOVENIA	6.000		
	ACGIH	NNN	10.000		A4 - LRT irr
	NATIONAL	AUSTRALIA	2.000		This value is for inhalable dust containing no asbestos and < 1% crystalline silica
	NATIONAL	AUSTRIA	4.000		Inhalable aerosol
	NATIONAL	BELGIUM	10.000		
	NATIONAL	DENMARK	2.000	4.000	Inhalable aerosol
	NATIONAL	FINLAND	5.000		
	NATIONAL	GERMANY	4.000		AGS; Inhalable aerosol
	NATIONAL	GERMANY	4.000		DFG; Inhalable aerosol
	NATIONAL	IRELAND	6.000		Inhalable fraction
	NATIONAL	IRELAND	2.400		Respirable fraction
	NATIONAL	LATVIA	1.000		
	NATIONAL	SWITZERLAND	4.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	6.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	2.400		Respirable aerosol
	NATIONAL	ESTONIA	2.000		
	NATIONAL	SLOVENIA	4.000		Inhalable fraction
	NATIONAL	FRANCE	10.000		Respirable aerosol
Aluminium oxide	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000		Inhalable aerosol
	NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	4.000		Respirable aerosol
	NATIONAL	AUSTRALIA	10.000		Inhalable dust containing no asbestos and < 1% crystalline silica
	NATIONAL	AUSTRIA	10.000	20.000	Long term: inhalable fraction; Short term: inhalable fraction, 60 minutes average value
	NATIONAL	AUSTRIA	5.000	10.000	Long term: respirable fraction; Short term: respirable fraction,

							60 minutes average value
	NATIONAL	DENMARK	5.000		10.000		Calculated as AI; Long term and Short term: inhalable aerosol
	NATIONAL	DENMARK	2.000		4.000		Calculated as AI; Long term and Short term: respirable aerosol
	NATIONAL	GERMANY	4.000				Inhalable aerosol
	NATIONAL	GERMANY	1.500				Respirable aerosol
	NATIONAL	HUNGARY	6.000				Respirable aerosol
	NATIONAL	IRELAND	10.000				Inhalable fraction
	NATIONAL	IRELAND	4.000				Respirable fraction
	NATIONAL	LATVIA	6.000				
	NATIONAL	POLAND	2.500		16.000		Dz. U. 2018 poz. 1286 wraz z późn. zm
	NATIONAL	POLAND	1.200				Aluminium trioxide as AI fume; Long term: respirable dust
	NATIONAL	ROMANIA	2.000	0.500	5.000	1.200	Long term and short term: aerosol
	NATIONAL	SPAIN	10.000				Inhalable aerosol
	NATIONAL	SPAIN	5.000				Respirable aerosol
	NATIONAL	SWEDEN	5.000				Inhalable aerosol
	NATIONAL	SWEDEN	2.000				Respirable aerosol
	NATIONAL	SWITZERLAND	3.000				Respirable aerosol
citral	NATIONAL	BELGIUM	32.000	5.000			Long term and short term: inhalable fraction and vapour; Additional indication "D" means that the absorption of the agent through the skin, mucous membranes or eyes is an important part of the total exposure.
	NATIONAL	POLAND	27.000		54.000		
	NATIONAL	SPAIN		5.000			
	NATIONAL	IRELAND		5.000			
	ACGIH	NNN		5.000			(IFV), Skin, DSEN, A4 - Body weight eff, URT irr, eye dam
(R)-p-mentha-1,8-diene	NATIONAL	FINLAND	140.000	25.000	280.000	50.000	
	NATIONAL	GERMANY	28.000	5.000	110.000	20.000	AGS
	NATIONAL	GERMANY	28.000	5.000	112.000	20.000	DFG
	NATIONAL	SWITZERLAND	40.000	7.000	80.000	14.000	
	NATIONAL	SLOVENIA	28.000	5.000	112.000	20.000	
	NATIONAL	SPAIN	168.000	30.000			
2,6-di-tert-butyl-p-cresol	NATIONAL	AUSTRALIA	10.000				
	NATIONAL	AUSTRIA	10.000				
	NATIONAL	BELGIUM	2.000				Inhalable fraction and vapour
	NATIONAL	DENMARK	10.000		20.000		
	NATIONAL	FINLAND	10.000		20.000		
	NATIONAL	FRANCE	10.000				
	NATIONAL	GERMANY	10.000		40.000		ASG; Long term and short term: inhalable aerosol and vapour

NATIONAL	GERMANY	10.000	40.000	DFG; Long term and short term: inhalable fraction and vapour
NATIONAL	IRELAND	10.000		
NATIONAL	SWITZERLAND	10.000		Inhalable aerosol
NATIONAL	SWITZERLAND		40.000	
NATIONAL	UNITED KINGDOM OF GREAT BRITAIN AND NORTHERN IRELAND	10.000		
NATIONAL	BULGARIA	10.000	50.000	
NATIONAL	CROATIA	10.000		
NATIONAL	PORTUGAL	2.000		
NATIONAL	SLOVENIA	10.000	40.000	
NATIONAL	SPAIN	10.000		
ACGIH	NNN	2.000		(IFV), A4 - URT irr

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1	4.340 µg/l	Freshwater	
		43.400 µg/l	Intermittent releases (freshwater)	
		434.000 ng/L	Marine water	
		3.840 mg/l	Microorganisms in sewage treatments	
		434.020 mg/kg	Freshwater sediments	
		43.400 mg/kg	Marine water sediments	
		86.780 mg/kg	Soil	
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction		2.630 µg/l	Freshwater	
		26.300 µg/l	Intermittent releases (freshwater)	
		263.000 ng/L	Marine water	
		7.210 mg/l	Microorganisms in sewage treatments	
		263.010 mg/kg	Freshwater sediments	
		26.301 mg/kg	Marine water sediments	
		58.580 mg/kg	Soil	
Amines, polyethylenepoly-, tetraethylenepentamine fraction	90640-66-7	6.800 µg/l	Freshwater	
		68.000 µg/l	Intermittent releases (freshwater)	
		680.000 ng/L	Marine water	
		4.600 mg/l	Microorganisms in sewage treatments	

titanium dioxide	13463-67-7	341.000 µg/kg	Freshwater sediments
		764.000 µg/kg	Marine water sediments
		274.000 µg/kg	Soil
		230.000 µg/kg	Secondary poisoning
		0.184 mg/l	Freshwater
		0.018 mg/l	Marine water
		1.000 mg/kg	Intermittent releases (freshwater)
		100.000 mg/kg	Intermittent releases (marine water)
		100.000 mg/kg	Microorganisms in sewage treatments
		26.800 µg/l	Freshwater
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	200.000 µg/l	Intermittent releases (freshwater)
		2.680 µg/l	Marine water
		20.000 µg/l	Intermittent releases (marine water)
		130.000 µg/l	Microorganisms in sewage treatments
		8.572 mg/kg	Freshwater sediments
		857.200 µg/kg	Marine water sediments
		1.250 mg/kg	Soil

Derived No Effect Level (DNEL) values

Component	CAS-No.	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	68082-29-1		3.900 mg/m ³	970.000 µg/m ³	Human Inhalation	Long Term, systemic effects
			1.100 mg/kg	560.000 µg/kg	Human Dermal	Long Term, systemic effects
				560.000 µg/kg	Human Oral	Long Term, systemic effects
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction			3.900 mg/m ³	970.000 µg/m ³	Human Inhalation	Long Term, systemic effects
			1.100 mg/kg	560.000 µg/kg	Human Dermal	Long Term, systemic effects
				560.000 µg/kg	Human Oral	Long Term, systemic effects
Amines, polyethylenepoly-, tetraethylenepentamine fraction	90640-66-7		1.290 mg/m ³	380.000 µg/m ³	Human Inhalation	Long Term, systemic effects
			6940.000 mg/m ³	2071.000 mg/m ³	Human Inhalation	Short Term, systemic effects
			740.000 µg/kg	320.000 µg/kg	Human Dermal	Long Term, systemic effects
				10.000 mg/kg	Human Dermal	Short Term, systemic effects

		0.036 mg/cm ²	0.560 mg/cm ²	Human Dermal	Long Term, local effects
			1.290 mg/cm ²	Human Dermal	Short Term, systemic effects
			530.000 µg/kg	Human Oral	Long Term, systemic effects
			26.000 mg/kg	Human Oral	Short Term, systemic effects
titanium dioxide	13463-67-7	10.000 mg/m ³		Human Inhalation	Long Term, local effects
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	540.000 µg/m ³	96.000 µg/m ³	Human Inhalation	Long Term, systemic effects
			140.000 µg/kg	Human Oral	Long Term, systemic effects

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.(EN166)

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Protection for hands:

Suitable materials for safety gloves; EN 374:

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Respiratory protection:

N.A.

Thermal Hazards:

N.A.

Environmental exposure controls:

N.A.

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid

Color: Yellow

Odour: Like: Amines

Odour threshold: N.A.

pH: =10.30

Kinematic viscosity: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: $> 90\text{ }^{\circ}\text{C}$ (194 $^{\circ}\text{F}$)

Flash point: Not Applicable

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.62 g/cm³

Solubility in water: Miscible

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Flammability: N.A.

Volatile Organic compounds - VOCs = 0.94 % ; 15.27 g/l

Particle characteristics:

Particle size: N.A.

9.2. Other information

Miscibility: N.A.

Conductivity: N.A.
Evaporation rate: N.A.
Viscosity: 14,000.00 cPo
No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Data not available.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye Dam. 1(H318)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	a) acute toxicity	LD50 Oral Rat > 2000.00000 mg/kg	
		LD50 Skin Rat > 2000.00000 mg/kg 24h	
	c) serious eye damage/irritation	Eye Irritant Yes 1h	
		Eye Corrosive Rabbit Positive	
	d) respiratory or skin sensitisation	Skin Sensitization Positive	Mouse
	g) reproductive toxicity	No Observed Adverse Effect Level Oral Rat = 1000.00000 mg/kg	
Reaction product of fatty acids, C18 alkyl with	a) acute toxicity	LD50 Oral Rat > 2000.00000 mg/kg	

amines, polyethylenepoly-
tetraethylenepentamine
fraction

LD50 Skin Rat > 2000.00000 mg/kg 24h

b) skin corrosion/irritation Skin Irritant Negative

c) serious eye damage/irritation Eye Corrosive Positive

d) respiratory or skin sensitisation Skin Sensitization Positive

Mouse

g) reproductive toxicity No Observed Adverse Effect Level Oral Rat = 1000.00000 mg/kg

Alcohols, C12-15,
branched and linear,
ethoxylated

a) acute toxicity LD50 Oral > 300.00 mg/kg

Amines,
polyethylenepoly-,
tetraethylenepentamine
fraction

a) acute toxicity LD50 Oral Rat = 1861.90000 mg/kg

LD50 Skin Rabbit = 1465.40000 mg/kg 24h

b) skin corrosion/irritation Skin Corrosive Rabbit Positive

c) serious eye damage/irritation Eye Irritant Rabbit Yes

d) respiratory or skin sensitisation Skin Sensitization Guineapig Positive

f) carcinogenicity Genotoxicity Negative

Mouse intraperitoneal rout

g) reproductive toxicity Reproductive Toxicity Oral Rat Negative

Quartz

a) acute toxicity LD50 Oral > 2000.00000 mg/kg

titanium dioxide

a) acute toxicity LD50 Oral Rat > 5000.00 mg/kg

LC50 Inhalation > 6.82 mg/l

d) respiratory or skin sensitisation Skin Sensitization Negative

i) STOT-repeated exposure No Observed Adverse Effect Level 1000.00

Amines,
polyethylenepoly-,
triethylenetetramine
fraction

a) acute toxicity LD50 Oral Rat = 1716.20000 mg/kg

LD50 Skin Rabbit = 1465.40000 mg/kg 24h

b) skin corrosion/irritation Skin Corrosive Rabbit Positive

c) serious eye damage/irritation Eye Irritant Rabbit Yes

d) respiratory or skin sensitisation Skin Sensitization Guineapig Positive

f) carcinogenicity Genotoxicity Negative

Mouse intraperitoneal rout

Carcinogenicity Skin = 50.00000 mg/kg

Mouse NOAEL

11.2 Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	CAS: 68082-29-1 - EINECS: 500-191-5	a) Aquatic acute toxicity : LC50 Fish = 10.00 mg/L 96h
		a) Aquatic acute toxicity : EC100 Daphnia = 10.00 mg/L 24h
		a) Aquatic acute toxicity : EC50 Algae = 4.34 mL/L 72h
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	EINECS: 701-046-0	a) Aquatic acute toxicity : LC50 Fish Zebrafish = 7.07000 mg/L 96h OECD 203
		a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 5.18000 mg/L 48h OECD 202
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 2.63000 mg/L 72h OECD 201
		a) Aquatic acute toxicity : EC50 Sludge Activated sludge = 721.00000 mg/L 3h OECD 209
		c) Bacteria toxicity : NOEC 1.41000 mg/L
Alcohols, C12-15, branched and linear, ethoxylated	CAS: 106232-83-1	a) Aquatic acute toxicity : LC50 Fish Carassius Auratus < 10.00 mg/L 96h CESIO
		a) Aquatic acute toxicity : EC50 Honeybees Daphnie < 10.00 mg/L 48h CESIO
Amines, polyethylenepoly-, tetraethylenepentamine fraction	CAS: 90640-66-7 - EINECS: 292-587-7	a) Aquatic acute toxicity : LC50 Fish freshwater fish = 420.00000 mg/L
		a) Aquatic acute toxicity : LC50 freshwater invertebrates = 24.10000 mg/L
		a) Aquatic acute toxicity : EC50 Algae freshwater algae = 6.80000 mg/L
		a) Aquatic acute toxicity : EC50 microorganisms = 97.30000 mg/L
		a) Aquatic acute toxicity : NOEC Algae = 0.50000 mg/L
titanium dioxide	CAS: 13463-67-7 - EINECS: 236-675-5 - INDEX: 022-006-00-2	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas (Cavedano americano) > 1000.00 mg/L 96h
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata (alghe cloroficee) > 100.00 mg/L 72h
		a) Aquatic acute toxicity : NOEC Algae = 5600.00 mg/L
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna (Pulce d'acqua grande) > 100.00 mg/L 48h
Amines, polyethylenepoly-, triethylenetetramine fraction	CAS: 90640-67-8 - EINECS: 292-588-2 - INDEX: 612-059-00-5	a) Aquatic acute toxicity : LC50 Fish Pimephales promelas = 330.00000 mg/L 96h „U.S EPA- TSCA, 40 CFR Part 797 1400
		a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna = 31.10000 mg/L 48h EU Method C.2 (Acute Toxicity for Daphnia)
		a) Aquatic acute toxicity : EC50 Algae Pseudokirchneriella subcapitata = 20.00000 mg/L 72h OECD 201
		d) Terrestrial toxicity : NOEC Worm Eisenia fetida = 62.50000 mg/kg OECD Guideline 222 (Earthworm Reproduction Test (Eisenia fetida/Eisenia andrei)) - 56days
		a) Aquatic acute toxicity : NOEC Algae soil microorganisms = 72.00000 mg/L

12.2. Persistence and degradability

Component	Persistence/Degradability:	Duration	Notes
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Non-readily biodegradable		OECD 301 D
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	Non-readily biodegradable		
Alcohols, C12-15, branched and linear, ethoxylated	Readily biodegradable	28d	>70% (OECD tg 301 B)
Amines, polyethylenepoly-, tetraethylenepentamine fraction	Non-readily biodegradable		
Amines, polyethylenepoly-, triethylenetetramine fraction	Non-readily biodegradable		OECD 301D

12.3. Bioaccumulative potential

Component	Bioaccumulation	Test	Value	Notes
Fatty acids, c18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	Bioaccumulative	BCF - Bioconcentration factor	77.400	L/kg ww; QSAR
Reaction product of fatty acids, C18 alkyl with amines, polyethylenepoly-tetraethylenepentamine fraction	Bioaccumulative	BCF - Bioconcentration factor	138.000	L/kg ww

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6 Endocrine disrupting properties

No endocrine disruptor substances present in concentration $\geq 0.1\%$

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

A waste code according to European waste catalogue (EWC) cannot be specified, due to dependence on the usage. Contact an authorized waste disposal service.

Properties of waste which render it hazardous (Annex III, Directive 2008/98/EC):

N.A.

SECTION 14: Transport information

14.1. UN number or ID number

N/A

14.2. UN proper shipping name

ADR-Shipping Name: N/A

IATA-Technical name: N/A

IMDG-Technical name: N/A

14.3. Transport hazard class(es)

ADR-Class: N/A

IATA-Class: N/A

IMDG-Class: N/A

14.4. Packing group

ADR-Packing Group: N/A

IATA-Packing group: N/A

IMDG-Packing group: N/A

14.5. Environmental hazards

Marine pollutant: No

Environmental Pollutant: No

IMDG-EMS: N/A

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR-Label: N/A

ADR - Hazard identification number: N/A

ADR-Special Provisions: N/A

ADR-Transport category (Tunnel restriction code): N/A

ADR Limited Quantities: N/A

ADR Excepted Quantities: N/A

Air (IATA) :

IATA-Passenger Aircraft: N/A

IATA-Cargo Aircraft: N/A

IATA-Label: N/A

IATA-Subsidiary hazards: N/A

IATA-Erg: N/A

IATA-Special Provisioning: N/A

Sea (IMDG) :

IMDG-Stowage Code: N/A

IMDG-Stowage Note: N/A

IMDG-Subsidiary hazards: N/A

IMDG-Special Provisioning: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2020/878

Regulation (EC) nr 648/2004 (Detergents).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3

Restrictions related to the substances contained: 28, 40, 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) 649/2012 (PIC regulation):

No Substance Listed

German Water Hazard Class.
Class 3: extremely hazardous.
SVHC Substances:
No data available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
------	-------------

EUH071	Corrosive to the respiratory tract.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H351	Suspected of causing cancer if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1-1A-1B	Skin Sens. 1,1A,1B	Skin Sensitisation, Category 1,1A,1B
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.6/2	Carc. 2	Carcinogenicity, Category 2
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
3.3/1	Calculation method
3.4.2/1A	Calculation method
4.1/C3	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ATE: Acute Toxicity Estimate
 ATEmix: Acute toxicity Estimate (Mixtures)
 BCF: Biological Concentration Factor
 BEI: Biological Exposure Index
 BOD: Biochemical Oxygen Demand
 CAS: Chemical Abstracts Service (division of the American Chemical Society).
 CAV: Poison Center
 CE: European Community
 CLP: Classification, Labeling, Packaging.
 CMR: Carcinogenic, Mutagenic and Reprotoxic
 COD: Chemical Oxygen Demand
 COV: Volatile Organic Compound
 CSA: Chemical Safety Assessment
 CSR: Chemical Safety Report
 DMEL: Derived Minimal Effect Level
 DNEL: Derived No Effect Level.
 DPD: Dangerous Preparations Directive
 DSD: Dangerous Substances Directive
 EC50: Half Maximal Effective Concentration
 ECHA: European Chemicals Agency
 EINECS: European Inventory of Existing Commercial Chemical Substances.
 ES: Exposure Scenario
 GefStoffVO: Ordinance on Hazardous Substances, Germany.
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
 IARC: International Agency for Research on Cancer
 IATA: International Air Transport Association.
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
 IC50: half maximal inhibitory concentration
 ICAO: International Civil Aviation Organization.
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
 IMDG: International Maritime Code for Dangerous Goods.
 INCI: International Nomenclature of Cosmetic Ingredients.
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care
 KAFH: Keep Away From Heat
 KSt: Explosion coefficient.
 LC50: Lethal concentration, for 50 percent of test population.
 LD50: Lethal dose, for 50 percent of test population.
 LDLo: Leathal Dose Low
 N.A.: Not Applicable
 N/A: Not Applicable
 N/D: Not defined/ Not available
 NA: Not available
 NIOSH: National Institute for Occupational Safety and Health
 NOAEL: No Observed Adverse Effect Level
 OSHA: Occupational Safety and Health Administration.
 PBT: Persistent, Bioaccumulative and Toxic
 PGK: Packaging Instruction
 PNEC: Predicted No Effect Concentration.
 PSG: Passengers
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
 STEL: Short Term Exposure limit.
 STOT: Specific Target Organ Toxicity.
 TLV: Threshold Limiting Value.
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
 vPvB: Very Persistent, Very Bioaccumulative.
 WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES

- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 13. DISPOSAL CONSIDERATIONS
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION