

Detailed installation statements and methodologies will vary for all sites as each will have different aspects deserving particular consideration, consequently the relevant approvals should be sought from the consulting engineer and/or the installer. 0

.

2

E1-E01-037-3

.

dations for BS EN 1433:2002 load class requirements.		
al and lateral loads depends upon A) ground conditions B) stability of the adjacent nended installation detail may require the minimum dimensions to be revised to re).		
. In any temporary condition, i.e. with the channel walls projecting above fill or cover plates will not protect the channel walls or grating. A temp lly, to 3 - 6mm above top of edge rail, either side of a channel for a dist I be adequate to carry the site traffic.	orary	
st a channel must be laid as a soldier course and restrained from move nodified mortar for bed and perpendicular joints (e.g. RONAFIX mortar should be set at a higher level to compensate for possible settlement o	mix C or	
nnel edge rail. The installer must ensure that the finished surface level the grating, before concreting the haunch or laying blocks, removes the aterial and embedded stones. (Please note that ACO channels must be	e time and	I
s are to be sealed, an appropriate sealant should be used (e.g. Sikafle ning should be sought from the sealant manufacturer.	x 11FC or	
n dust, oil, and grease, with any loose material or dirt removed, e.g. by	mechanical	
with no flaws. The detail on the ends of a channel varies from one product to		
er approximately 5mm thick to one face of the joint. e sealant in a bead of approximately 10mm diameter into the sealing groove. the channel - apply the sealant to the end face of the channel and to the e sealant will both cover the end face and fill the groove. bedding and pressed against the previously placed channel unit. A sealed joint of sent channel units. hannel to leave a smooth finish. he the sealant should be kept as dry as possible.		(
stance to concrete and mortar products but may experience corrosion i concrete and consider using corrosion inhibitors where necessary. The	•	
n.		1
		1
	Nema	L
	Name Revision: A	
	NEVISIUII. A	
CO HEXDRAIN BRICKSLOT CHANNEL INSTALLATION DETAIL DRAWING		

6

$\square \oplus$	Units: mm	Format: A3
		Scale: 1:5
n contained in this drawing is copyright property of ACO ies plc. Any reproduction in part or whole without written ermission of ACO Technologies plc is prohibited		Sheet: 1 of 1
		<u>^</u>