

Rotary Hammer with SDS max

GBH 5-40 DCE



Bosch's SDS max rotary hammer for comfortable handling in extensive applications

The most important data

Rated input power	1,150 W
Impact energy (according to EPTA 05/2016)	8.8 J
Drilling dia. concrete, hammer drill bits	12 – 40 mm

Part Number 0 611 264 070

> More product information

Technical data

Performance data

Impact rate at rated speed	1,500 – 2,980 bpm
Rated speed	165 – 330 rpm
Technical data	
Rated input power	1,150 W
Impact energy (according to EPTA 05/2016)	8.8 J
Tool holder	SDS max
Packaging dimensions (width x length x height)	410 x 615 x 145 mm
Voltage, electrical	240 V
Weight	6.8 kg
Drilling range	
Drilling dia. concrete, hammer drill bits	12 – 40 mm
Opt. appl. range concrete, hammer drill bits	18 – 32 mm
Drilling dia. concrete, breakthrough drill bits	45 – 55 mm
Drilling diameter in concrete with core cutters	40 – 90 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	16.2 m/s²
Uncertainty K	1.5 m/s²
Chiselling in concrete	
Vibration emission value ah	10.5 m/s²
Uncertainty K	1.5 m/s²

Product data sheet Power tools for trade & industry



Advantages:

- Vibration Control and lightweight design for effortless and continuous work in time-intensive applications
- Durable due to robust metal components and optimised lubrication system
- Powerful motor enables the delivery of 8.8 J of impact energy for fast drilling and high removal rate

