



DECLARATION OF PERFORMANCE:

THE CONSTRUCTION PRODUCTS (AMENDMENT ETC.)

(EU EXIT) REGULATIONS 2020 NO 1359

This UK declaration of the performance from Knauf UK Ltd covers all essential characteristics required and specified by EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations



DOP NO.0085_AQUAPANEL_Cement_Board_Indoor_2022_08_15_DOP_UKCA

1. Unique identification code of the product-type:

AQUAPANEL Cement Board Indoor

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

AQUAPANEL Cement Board

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Aquapanel cement board indoor for use in construction of indoor walls and ceilings especially in wet and humid areas.

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5):

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D – 58638 Iserlohn – Tel:+49 2374 5036-0, Fax: +49 5036-300, E-mail: aquapanel.info@knauf.com

5. Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Knauf UK Ltd, Kemsley Fields Business Park, Sittingbourne, Kent, ME9 8SR. Tel.: +441795-424499 Fax: +441795-428651 Email: info@knauf.co.uk

6. System (AVCP) or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 and 4

6a) Notified Body/Bodies: Not Applicable

6b) European Technical Assessment - ETA – 07/0856

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN12467:2012+A2:2018

8. Declared Performance.

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	A1 (according to EN 13501-2018)	EN12467:2012+A2:2018
Mechanical resistance	Class 2	EN12467:2012+A2:2018
Release of dangerous substances	NPD	EN12467:2012+A2:2018
Durability against warm water	RL≥0.75	EN12467:2012+A2:2018
Durability against soak/dry	RL≥0.75	EN12467:2012+A2:2018
These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use. Performance declared is for the system of which the product is a part of.		

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies.

Not Applicable

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ian Stokes, Managing Director
Sittingbourne

Creation Date: 15/08/2022
Revision Ref. 001
Revision Date: 15/08/2022



Build for the world we live in