



# waterproof 1C tape

For use with BAL Waterproof 1C as part of a waterproofing system

## Use for

- Part of an EAD certified system with BAL Waterproof 1C to ensure NHBC compliant shower and wet-room installations prior to tiling.
- Reinforcing corners and junctions.
- Wall junction with bases/upstands/columns
- Static, stable cracks and joints in the background/base
- Suitable for domestic and commercial use
- Suitable for internal applications in wet environments

## PRODUCT INFORMATION

**Composition:** Polyester fleece (PES Filament)

**Colour:** White

**Pack sizes:** 5 metre roll

## SURFACE PREPARATION

### General

Ensure that surfaces are clean, sound, free from dust, contaminants and barriers to adhesion.

### APPLICATION

BAL WATERPROOF 1C TAPE is to be used as part of a waterproofing system with BAL WATERPROOF 1C where an EAD certified system is required.

Using a suitable brush, roller or trowel, apply BAL WATERPROOF 1C at a minimum wet thickness of 1.0mm (0.8mm dry thickness) to at least 50mm either side of the crack/junction/corner. Then apply BAL WATERPROOF 1C TAPE, by thoroughly pushing the TAPE into the coating so that the coating penetrates evenly through the TAPE and ensuring that there are no wrinkles. Immediately apply a second coat of BAL WATERPROOF 1C at a minimum wet thickness of 1.0mm (0.8mm dry thickness) to at least 50mm either side of the crack/junction/corner. This applies to:

- Internal and external corners of walls/partitions
- Wall junctions with bases/upstands/columns
- Junctions of different bases/background materials
- Static, stable cracks and joints in the background/base

Please refer to the NHBC install guide for BAL WATERPROOF 1C for full details.

### ARDEX GROUP WARRANTY

ARDEX Group supplies products under a range of Brands into the UK and Ireland markets. This Warranty applies to BAL, ARDEX, Gutjahr, Wakol, Loba, Wedi or Knopp products whether used individually or in combination provided they are used in accordance with the relevant product datasheets and the warranty terms and conditions are available on the website. This Warranty applies only to Products purchased and used in the UK and Ireland directly from one of the Brands or a Brand authorised stockist.

## HEALTH & SAFETY INFORMATION / GOOD PRACTICE ADVICE

For detailed information and safety guidance, please refer to Product Material Safety Data Sheet [MSDS].

### TECHNICAL ADVISORY SERVICE

For free expert guidance on use of this product, or any aspect of tiling, contact the BAL TECHNICAL ADVISORY AND SPECIFICATION SERVICE on Tel: 01782 591120 or 03330 030160 or Email: [info@building-adhesives.com](mailto:info@building-adhesives.com)

### SHELF LIFE

12 months under normal dry conditions. Protect from frost and damp.

### QUALITY AND ENVIRONMENTAL STANDARDS

Manufacturing quality assurance standards conform to BS EN ISO 9001. Satisfies the environmental management requirements and operational scope of ISO 14001.

### 25 YEAR GUARANTEE

All BAL products are supplied with a 25-year product guarantee to be free from manufacturing defects and to be fit for purpose. The guarantee covers materials replacement costs and labour. This guarantee is subject to use of product in accordance with BAL's instructions and technical data, and good working practice. No liability can be accepted for any loss or damage arising from incorrect use of products or poor workmanship, over which BAL has no control. While products may be suitable for installations internally or externally, products when used externally are exempt from cover under the BAL 25 Year Guarantee. Terms and conditions apply. Full details are available for your review at [www.bal-adhesives.com](http://www.bal-adhesives.com).

### CONDITIONS OF SALE

Sold subject to the Company's Conditions of Sale. *Available on request.*

*For sales and technical queries, contact:*

### BUILDING ADHESIVES LTD

Longton Road, Trentham, Stoke-on-Trent, ST4 8JB, England  
[www.bal-adhesives.com](http://www.bal-adhesives.com)

Sales

Tel: +44 (0) 1782 591160

Fax: +44 (0) 1782 591131

Technical

Tel: +44 (0) 1782 591120 or

+44 (0) 3330 030160

Email: [info@building-adhesives.com](mailto:info@building-adhesives.com)

Ireland

Unit 622, Phase III

Northwest Business Park

Ballycoolin, Dublin 15, Ireland

Tel: +353 (0) 1 880 9210

Fax: +353 (0) 1 880 9211

NOTE: BAL reserves the right to update instructions, technical data and other information at any time without notice.

PorcelBond Plus™ is a trademark of Building Adhesives Ltd