
Product data sheet





Rotary Hammer with SDS plus

GBH 2-26



All-round performance rotary hammer for daily use in the SDS plus category

The most important data

Rated input power	830 W
Impact energy (according to EPTA 05/2016)	2.7 J
Drilling dia. concrete, hammer drill bits	4 – 26 mm

Part Number 0 611 2A3 060

> More product information

Technical data

Performance data

Impact rate at rated speed	0 - 4,000 bpm
Rated speed	0 – 900 rpm
Technical data	
Rated input power	830 W
Impact energy (according to EPTA 05/2016)	2.7 J
Tool holder	SDS plus
Packaging dimensions (width x length x height)	443 x 117 x 362 mm
Voltage, electrical	110 V
Weight	2.7 kg
Drilling range	
Drilling dia. concrete, hammer drill bits	4 – 26 mm
Opt. appl. range concrete, hammer drill bits	8 – 16 mm
Drilling diameter in concrete with core cutters	16 – 68 mm
Max. drilling diameter in metal	13 mm
Max. drilling diameter in wood	30 mm

Noise/vibration information

Hammer drilling in concrete

Vibration emission value ah	16.5 m/s ²
Uncertainty K	1.5 m/s ²
Chiselling in concrete	
Vibration emission value ah	12.1 m/s²
Uncertainty K	1.5 m/s ²

Invented for life

Product data sheet

Power tools for trade & industry

Advantages:

- Delivers 2.7 J of impact energy for fast drilling and high chisel removal performance
- High-quality components ensure robustness, reliability, and long performance lifetime
- Optional chisel mode enables use in wide range of applications















