



ProClean

GROUT HAZE REMOVER

CEMENT & GROUT
RESIDUE CLEANER

ProClean GROUT HAZE REMOVER

CEMENT & GROUT
RESIDUE CLEANER

- Effortlessly removes cement, efflorescence and grouting residues
- Suitable to use on non-acid sensitive surfaces
- Fast-acting formula
- Internal & external use
- Removes pointing mortar residue

1L e



suitable for internal
and external use

1L

Product Selection Guide

Suitable surface & substrates:

✓	Sandstone	✓	Terracotta
✓	Porcelain	✓	Quarry Tile
✓	Slate	✓	Granite
✓	Ceramic	✓	Non acid-sensitive tiled surfaces

ULTRA[®]
TILE

TECHNICAL DATASHEET

DESCRIPTION

- Effortlessly removes cement, efflorescence & grouting residues
- Suitable to use on non-acid sensitive surfaces
- Easy to apply
- Fast-acting formula
- Internal & external use
- Removal of pointing mortar residue

UltraTile Grout Haze Remover effortlessly removes residues such as mortar and cement grout, efflorescence, encrusted and engrained dirt, as well as natural calcium & limescale deposits.

Use indoors and outdoors after installation process, it is suitable for all acid resistant surfaces, including ceramic tiles, porcelain, brick, clay and quarry tiles, terracotta, concrete and other types of natural stone.

Grout Haze Remover is not suitable for use with brushin sand grout or around acid sensitive surfaces such as enamel, zinc, chrome, stainless steel, polished marble and limestone, etc.

DIRECTIONS FOR USE

- 1) **Always perform a test in an inconspicuous area on-site to check suitability of product, prior to use - read these instructions fully before application. If you experience difficulties using this product, please contact our technical support team on the number above.**
- 2) Dependent on degree of contamination, Grout Haze Remover can be used neat or diluted up to 1:10 with clean water.
- 3) Pre-wet the surface, apply generously and allow the product to dwell for a few minutes before agitating and rinsing off with plenty of clean water.
- 4) Repeat the process if necessary. If using Grout Haze Remover indoors ensure good ventilation during and after use.

PLEASE NOTE: When using internally, ventilate working area by opening doors and windows.

COVERAGE

Up to 100m² per litre

Coverage will vary depending on surface contamination and dilution rate used.

POINTS OF NOTE

Please ensure that appropriate PPE is used when using this product. Protect sensitive surfaces as even minor splashes can

cause damage. Not suitable for day to day cleaning, if you require a mild catch-all cleaner we recommend Porcelain Tile & Stone Floor Cleaner. Always protect these areas. Always test this product in an inconspicuous area. It remains the responsibility of the end user to check the suitability of the product.

STORAGE

This product must be stored in unopened bottles, in a frost free environment out of direct sunlight. Avoid frost. Ideal storage temperatures are between 5°C and 25°C.

SHELF LIFE

Under the above storage conditions this product has a shelf life of 12 months from production date.

Precautions:

H314: Causes severe skin burns and eye damage. H290: May be corrosive to metals. H302: Harmful if swallowed. H302+312+332: Harmful if swallowed, in contact with skin or if inhaled. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H318: Causes serious eye damage. H335: May cause respiratory irritation. P264: Wash hands thoroughly after handling. P280: Wear eye protection. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P302+350: IF ON SKIN: Gently wash with plenty of soap and water. P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P333+313: If skin irritation or rash occurs: Get medical advice/attention. P337+313: If eye irritation persists: Get medical advice/attention.



HEALTH & SAFETY

Please ensure that appropriate PPE is used when preparing, mixing and applying products. Always wash hands before consuming food and make sure that materials are kept safely out of reach of children and animals. Please dispose of packaging and waste appropriately. A full Material Safety Data Sheet relating to this product is available to download online.



Read this guide in full. Always complete a test application before proceeding.
If you have any questions please contact our technical support team on 01827 254402.

Instarmac Group plc
Danny Morson Way, Birch Coppice Business Park
Dordon, Tamworth, Staffordshire B78 1SE
t: +44 (0)1827 254402
e: enquiries@instarmac.co.uk orders: orders@instarmac.co.uk

w: instarmac.co.uk

Vers 01.10.2022 Information correct at time of print. Uncontrolled if printed. For the most up-to-date version of this datasheet, please refer to this product's profile on our website which can be found at www.ultratileadhesives.co.uk



TECHNICAL DATASHEET

QUALITY ASSURANCE

All products are manufactured in a plant whose quality management system is certified as being in conformity with BE EN ISO 9001. Products are guaranteed against defective materials and manufacture and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept responsibility arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All UltraTile products are sold subject to our terms and conditions of sales, copies of which may be obtained upon request.

TECHNICAL DATA

Unit Size:	1L Bottle
Colours:	Red
Application Temperatures:	5°C to 25°C
ph Value:	1-2

USAGE GUIDELINES

Dwell Time Guidance:	2-5 minutes*
Applications / Coats:	1-2 applications
Application Method:	Sponge / Brush
Dilution:	Varies, see directions for use

*Depending on temperatures, substrate and site conditions.



Read this guide in full. Always complete a test application before proceeding.
If you have any questions please contact our technical support team on 01827 254402.

Instarmac Group plc
Danny Morson Way, Birch Coppice Business Park
Dordon, Tamworth, Staffordshire B78 1SE
t: +44 (0)1827 254402
e: enquiries@instarmac.co.uk orders: orders@instarmac.co.uk
w: instarmac.co.uk

Vers 01.10.2022 Information correct at time of print. Uncontrolled if printed. For the most up-to-date version of this datasheet, please refer to this product's profile on our website which can be found at www.ultratileadhesives.co.uk

